

Einstein's magnetic effect is measured on microscale

September 30 2006



In NIST's Einstein-de Haas experiment, the movements of a cantilever were measured with an optical-fiber laser interferometer. The optical fiber is 125 micrometers in diameter, and the end is positioned less than 10 micrometers from the cantilever surface. Credit: Credit: John Moreland/NIST

A gyromagnetic effect discovered by Albert Einstein and Dutch physicist Wander Johannes de Haas--the rotation of an object caused by a change in magnetization--has been measured at micrometer-scale dimensions for the first time at the National Institute of Standards and Technology.

The new method may be useful in the development and optimization of thin film materials for read heads, memories and recording media for magnetic data storage and spintronics, an emerging technology that relies on the spin of electrons instead of their charge as in conventional



electronics.

The Einstein-de Haas effect was first observed in experiments reported in 1915, in which a large iron cylinder suspended by a glass wire was made to rotate by an alternating magnetic field applied along the cylinder's central axis. By contrast, the NIST experiments, described in the Sept. 18 issue of *Applied Physics Letters*, measured the Einstein-de Haas effect in a ferromagnetic thin film only 50 nanometers thick deposited on a microcantilever--a tiny beam anchored at one end and projecting into the air. An alternating magnetic field induced changes in the magnetic state of the thin film, and the resulting torque bent the cantilever up and down by just a few nanometers.

Using a laser interferometer to measure the movements of the cantilever and comparing those data to changes in the magnetic state of the material, researchers were able to determine the "magnetomechanical ratio," or the extent to which the material twists in response to changes in its magnetic state. The magnetomechanical ratio is related to another important parameter, the "g-factor," a measure of the internal magnetic rotation of the electrons in a material in a magnetic field.

The magnetomechanical ratio and the g-factor are critical in understanding magnetization dynamics and designing magnetic materials for data storage and spintronics applications, but they are extremely difficult to determine accurately because of many potential complicating effects.

The NIST experiments provide a proof-of-concept for using the Einsteinde Haas effect to determine the magnetomechanical ratio and the related g-factor in thin ferromagnetic films. The researchers note that a number of improvements are possible, such as operating the cantilever system in a vacuum to reduce the effects of any changes in temperature.



Citation: T.M. Wallis, J. Moreland and P. Kabos. 2006. Einstein-de Haas effect in a NiFe film deposited on a microcantilever. *Applied Physics Letters*. Sept. 18.

Source: National Institute of Standards and Technology

Citation: Einstein's magnetic effect is measured on microscale (2006, September 30) retrieved 26 April 2024 from <u>https://phys.org/news/2006-09-einstein-magnetic-effect-microscale.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.