

Biologically inspired sensors can augment sonar, vision system in submarines

February 21 2007

To find prey and avoid being preyed upon, fish rely on a row of specialized sensory organs along the sides of their bodies, called the lateral line. Now, a research team led by Chang Liu at the University of Illinois at Urbana-Champaign has built an artificial lateral line that can provide the same functions in underwater vehicles.

"Our development of an artificial lateral line is aimed at enhancing human ability to detect, navigate and survive in the underwater environment," said Liu, a Willett Scholar and a professor of electrical and computer engineering at Illinois. "Our goal is to develop an artificial device that mimics the functions and capabilities of the biological system."

In fish, the lateral line provides guidance for synchronized swimming, predator and obstacle avoidance, and prey detection and tracking. Equipped with an artificial lateral line, a submarine or underwater robot could similarly detect and track moving underwater targets, and avoid collisions with moving or stationary objects.

The artificial lateral line consists of an integrated linear array of micro fabricated flow sensors, with the sizes of individual sensors and spacings between them matching those of their biological counterpart.

"By detecting changes in water pressure and movement, the device can supplement sonar and vision systems in submarines and underwater robots," said Liu, who also is affiliated with the university's Beckman

Institute for Advanced Science and Technology, the Institute for Genomic Biology, and the Micro and Nanotechnology Laboratory.

Liu and colleagues at Illinois and at Bowling Green State University described their work in the Dec. 12, 2006, issue of the *Proceedings of the National Academy of Sciences*.

To fabricate the tiny, three-dimensional structures, individual components are first cast in place on sacrificial layers using photolithography and planar deposition. A small amount of magnetic material is electroplated onto each of the parts, which are then freed from the substrate by an etchant. When a magnetic field is applied, the induced torque causes the pieces to rotate out of the plane on tiny hinges and lock into place.

Each sensor is integrated with metal-oxide-superconductor circuitry for on-chip signal processing, noise reduction and data acquisition. The largest array the researchers have built consists of 16 flow sensors with 1 millimeter spacing. Each sensor is 400 microns wide and 600 microns tall.

In tests, the researchers' artificial lateral line was able to localize a nearby underwater vibrating source, and could detect the hydrodynamic wake (such as the wake formed behind a propeller-driven submarine) for long-distance tracking. With further advances in engineering, man-made underwater vehicles should be able to autonomously image hydrodynamic events from their surroundings, Liu said.

"Although biology remains far superior to human engineering, having a man-made parallel of the biological system allows us to learn much about both basic science and engineering," Liu said. "To actively learn from biology at the molecular, cellular, tissue and organism level is still the bigger picture."

Source: University of Illinois at Urbana-Champaign

Citation: Biologically inspired sensors can augment sonar, vision system in submarines (2007, February 21) retrieved 19 April 2024 from <https://phys.org/news/2007-02-biologically-sensors-augment-sonar-vision.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.