

MIT upgrades Sputnik-era antenna

August 13 2008, By Gregory P. Hamill

(PhysOrg.com) -- A mammoth MIT antenna installed in 1957 as the first radar system to conduct space surveillance (it observed the Sputnik satellite) is poised for many more years of key observations thanks to a recently completed renovation.

Lincoln Laboratory's Millstone Hill Radar (MHR) antenna is one of the world's principal tools for maintaining the Deep Space Catalog--the listing of the more than 3000 objects circling the Earth 40,000 km away in geosynchronous earth orbit (GEO). Together with two other surveillance radars--ARPA Long-Range Tracking and Instrumentation Radar (ALTAIR, in the Marshall Islands) and Globus II (in Norway), it monitors the increasingly cluttered geosynchronous orbit to reduce the probability of collisions. The three also monitor satellite and spacecraft launches.

But the venerable MHR system was showing its age. The motors and motor generators replaced in this renovation were original 1950s era equipment. "They were past their end of life. The motors were worn from years of use and regular rebuilds, and the inefficient motor generators were failing frequently," says Paula Ward of Lincoln's Control Systems Engineering group. Each failure would shut down the antenna for a significant period of time.

Now the system, which consists of an 84-foot-diameter (25 m) reflector supported by a tower a little over 85 feet high (26 m), is easier to troubleshoot, and downtime can be kept to a minimum.

Jeff Dominick, the site manager of the Lincoln Space Surveillance Complex (LSSC) that includes MHR, stresses the importance of MHR to LSSC and how important LSSC, in turn, is to the Air Force Space Command. "Losing MHR for any period of time would impact our ability to track in this region," he says, pointing to the arc of GEO above the United States that isn't covered by ALTAIR and Globus II.

As project lead of the recent upgrade, Ward was working with two extremes--very heavy and bulky motors and gear boxes, and new software controls running in a real-time embedded environment.

For example, installing and aligning the new motors and gear boxes was challenging since no mechanical computer-aided-design models existed. At the other end of the spectrum, while many upgrades had been done to the radar system and associated computers over the years, the antenna control system had been upgraded only twice in the last fifty years.

Prior to the upgrade, an operator needing to move the antenna for maintenance had to turn mechanical knobs to rotate the antenna and read meters on a panel indicating positions. Now the interface is more intuitive and is done on a laptop. The operator simply sets the desired positions, and clicks Run. In addition, the upgraded system provides, for the first time, remote access to the antenna's local displays.

Dominick concludes, "We're trying to reduce the probability of collisions. This upgrade has significantly reduced downtime and maintenance tasks associated with the MHR antenna control system."

Provided by MIT

<https://phys.org/news/2008-08-mit-sputnik-era-antenna.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.