


Smart Lighting: New LED Drops the 'Droop'

January 12 2009



Band diagram of conventional GaInN/GaN active region and new polarization-matched GaInN/GaN active region of a light-emitting diode.

(PhysOrg.com) -- Researchers at Rensselaer Polytechnic Institute have developed and demonstrated a new type of light emitting diode (LED) with significantly improved lighting performance and energy efficiency.

The new polarization-matched LED, developed in collaboration with Samsung Electro-Mechanics, exhibits an 18 percent increase in light output and a 22 percent increase in wall-plug efficiency, which essentially measures the amount of electricity the LED converts into light.

The new device achieves a notable reduction in “efficiency droop,” a well-known phenomenon that provokes LEDs to be most efficient when

receiving low-density currents of electricity, but then to lose efficiency as higher density currents of electricity are fed into the device. The cause of this droop is not yet fully understood, but studies have shown that electron leakage is likely a large part of the problem.

“This droop is under the spotlight since today’s high-brightness LEDs are operated at current densities far beyond where efficiency peaks,” said project leader E. Fred Schubert, Wellfleet Senior Constellation Professor of Future Chips at Rensselaer, and head of the university’s National Science Foundation-funded Smart Lighting Engineering Research Center.

“This challenge has been a stumbling block, because reducing the current densities to values where LEDs are more efficient is unacceptable. Our new LED, however, which has a radically re-designed active region, namely a polarization-matched active region, tackles this issue and brings LEDs closer to being able to operate efficiently at high current densities,” Schubert said.

Results of the study are explained in a paper published online this week by Applied Physics Letters.

Focusing on the active region of LEDs where the light is generated, Schubert’s team discovered the region contained materials with mismatched polarization. The polarization mismatch likely causes electron leakage, and therefore a loss of efficiency, Schubert said.

The researchers discovered that the polarization mismatch can be strongly reduced by introducing a new quantum-barrier design. They replaced the conventional Gallium Indium Nitride/Gallium Nitride (GaInN/GaN) layer of the LED active region, and replaced it with Gallium Indium Nitride/ Gallium Indium Nitride (GaInN/GaInN). This substitution allows the layers of the active region to have a better

matched polarization, and in turn reduce both electron leakage and efficiency droop.

The benefits seen by testing the new GaInN/GaInN LED were consistent with theoretical simulations showing polarization matching reducing electron leakage and efficiency droop.

Schubert expects that a new wave of lighting devices based on LEDs and solid-state lighting will supplant the common light bulb in coming years, leading to vast environmental, energy, and cost benefits as well as innovations in healthcare, transportation systems, digital displays, and computer networking.

Along with Schubert, co-authors on the paper include Rensselaer physics, Future Chips, and electrical engineering graduate students Jiuru Xu, Martin F. Schubert, and Ahmed N. Noemaun; Rensselaer Future Chips research assistant Di Zhu; Jong Kyu Kim, research assistant professor of electrical, computer, and systems engineering at Rensselaer; along with Samsung Electro-Mechanics researchers Min Ho Kim, Hun Jae Chung, Sukho Yoon, Cheolsoo Sone, and Yongjo Park.

Funding for the project was contributed by Samsung Electro-Mechanics, the U.S. National Science Foundation, the Rensselaer Smart Lighting Engineering Research Center, Sandia National Laboratories, Rochester Institute of Technology, U.S. Department of Energy, U.S. Department of Defense, Magnolia Optics, Crystal IS, Troy Research Corporation, and New York state.

For more information on Rensselaer's Future Chips Constellation, visit: www.rpi.edu/futurechips/index.htm

Provided by Rensselaer Polytechnic Institute

Citation: Smart Lighting: New LED Drops the 'Droop' (2009, January 12) retrieved 1 May 2024 from <https://phys.org/news/2009-01-smart-droop.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.