

Gasoline-diesel 'cocktail': A potent recipe for cleaner, more efficient engines

August 3 2009, by Brian Mattmiller



Gasoline Pumps. Image: Wikipedia.

(PhysOrg.com) -- Diesel and gasoline fuel sources both bring unique assets and liabilities to powering internal combustion engines. But what if an engine could be programmed to harvest the best properties of both fuel sources at once, on the fly, by blending the fuels within the combustion chamber?

The answer, based on tests by the University of Wisconsin-Madison engine research group headed by Rolf Reitz, would be a diesel engine that produces significantly lower pollutant emissions than conventional engines, with an average of 20 percent greater fuel efficiency as well. These dramatic results came from a novel technique Reitz describes as "fast-response fuel blending," in which an engine's fuel injection is programmed to produce the optimal gasoline-diesel mix based on real-time operating conditions.

Under heavy-load operating conditions for a diesel truck, the fuel mix in Reitz' fueling strategy might be as high as 85 percent gasoline to 15 percent diesel; under lighter loads, the percentage of diesel would increase to a roughly 50-50 mix. Normally this type of blend wouldn't ignite in a diesel engine, because gasoline is less reactive than diesel and burns less easily. But in Reitz' strategy, just the right amount of diesel fuel injections provide the kick-start for ignition.

"You can think of the diesel spray as a collection of liquid spark plugs, essentially, that ignite the gasoline," says Reitz, the Wisconsin Distinguished Professor of Mechanical Engineering. "The new strategy changes the fuel properties by blending the two fuels within the combustion chamber to precisely control the combustion process, based on when and how much diesel fuel is injected."

Reitz will present his findings today (Aug. 3) at the 15th U.S. Department of Energy (DOE) Diesel Engine-Efficiency and Emissions Research Conference in Detroit. Reitz estimates that if all cars and trucks were to achieve the efficiency levels demonstrated in the project, it could lead to a reduction in transportation-based U.S. oil consumption by one-third.

"That's roughly the amount that we import from the Persian Gulf," says Reitz.

Two remarkable things happen in the gasoline-diesel mix, Reitz says. First, the engine operates at much lower combustion temperatures because of the improved control — as much as 40 percent lower than conventional engines — which leads to far less energy loss from the engine through heat transfer. Second, the customized fuel preparation controls the chemistry for optimal combustion. That translates into less unburned fuel energy lost in the exhaust, and also fewer pollutant emissions being produced by the combustion process. In addition, the

system can use relatively inexpensive low-pressure fuel injection (commonly used in gasoline engines), instead of the high-pressure injection required by conventional [diesel engines](#).

Development of the blending strategy was guided by advanced computer simulation models. These computer predictions were then put to the test using a Caterpillar heavy-duty diesel engine at the UW-Madison Engine Research Center. The results were "really exciting," says Reitz, confirming the predicted benefits of blended fuel combustion. The best results achieved 53 percent thermal efficiency in the experimental test engine. This efficiency exceeds even the most efficient diesel engine currently in the world — a massive turbocharged two-stroke used in the maritime shipping industry, which has 50 percent thermal efficiency.

"For a small engine to even approach these massive engine efficiencies is remarkable," Reitz says. "Even more striking, the blending strategy could also be applied to automotive gasoline engines, which usually average a much lower 25 percent thermal efficiency. Here, the potential for fuel economy improvement would even be larger than in diesel truck engines."

Thermal efficiency is defined by the percentage of fuel that is actually devoted to powering the engine, rather than being lost in heat transfer, exhaust or other variables.

"What's more important than fuel efficiency, especially for the trucking industry, is that we are meeting the EPA's 2010 emissions regulations quite easily," Reitz says.

That is a major commercial concern as the bar set by the U.S. Environmental Protection Agency is quite high, with regulations designed to cut about 90 percent of all particulate matter (soot) and 80 percent of all nitrogen oxides (NO_x) out of diesel emissions.

Some companies have pulled from the truck engine market altogether in the face of the stringent new standards. Many other companies are looking to alternatives such as selective catalytic reduction, in which the chemical urea (a second "fuel") is injected into the exhaust stream to reduce NO_x emissions. Others propose using large amounts of recirculated exhaust gas to lower the combustion temperature to reduce NO_x. In this case, ultra-high high-pressure fuel injection is needed to reduce soot formation in the combustion chamber.

Those processes are expensive and logistically complicated, Reitz says. Both primarily address cleaning up emissions, not fuel efficiency. The new in-cylinder fuel blending strategy is less expensive and less complex, uses widely available fuels and addresses both emissions and fuel efficiency at the same time.

Reitz says there is ample reason to believe the fuel-blending technology would work just as well in cars because dual dual-fuel combustion works with lower-pressure and less expensive fuel injectors than those used in diesel trucks. Applying this technology to vehicles would require separate tanks for both diesel and gasoline fuel — but so would urea, which is carried in a separate tank.

The big-picture implications for reduced oil consumption are even more compelling, Reitz says. The United States consumes about 21 million barrels of oil per day, about 65 percent (13.5 million barrels) of which is used in transportation. If this new blended fuel process could convert both [diesel](#) and [gasoline](#) engines to 53 percent thermal efficiency from current levels, the nation could reduce oil consumption by 4 million barrels per day, or one-third of all oil destined for transportation.

Computer modeling and simulation provided the blueprint for optimizing [fuel](#) blending, a process that would have taken years through trial-and-error testing. Reitz used a modeling technique developed in his

lab called genetic algorithms, which borrow some of the same techniques of natural selection in the biological world to determine the "fittest" variables for [engine](#) performance.

Source: University of Wisconsin-Madison ([news](#) : [web](#))

Citation: Gasoline-diesel 'cocktail': A potent recipe for cleaner, more efficient engines (2009, August 3) retrieved 30 March 2023 from <https://phys.org/news/2009-08-gasoline-diesel-cocktail-potent-recipe-cleaner.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.