

Envisat monitors oil spill proximity to Loop Current

May 5 2010



In this Envisat Advanced Synthetic Aperture Radar (ASAR) product for May 2, 2010, advanced processing methods have been performed to display ocean surface roughness variations and Doppler-derived ocean surface radial velocities around the oil spill area in the Gulf of Mexico. As visible, the spill still appears relatively confined around its point of origin and is still north of the Loop Current. An intriguing shape is detected in the image that seems to passively follow the flow derived from the Doppler measurements. Credit: CLS

As fears grow that the Loop Current in the Gulf of Mexico could soon catch the oil slick and drag it south towards coral reefs in the Florida Keys, scientists are monitoring the situation closely with ESA's Envisat radar data.



By combining surface roughness and current flow information with <u>Envisat</u> Advanced Synthetic Aperture Radar (ASAR) data of the spill, SAR image analysts are able to detect the direction in which the spill boundaries can drift.

In these two ASAR images for 29 April and 2 May, advanced processing methods have been performed to display ocean surface roughness variations and Doppler-derived ocean surface radial velocities. Merging this information provides insight into the spatial structure of the spill and its dispersion by the upper ocean turbulent flow.

In the 29 April image, smooth surfaces appear as black patches inside the oil spill and in the very low wind region east of the spill, where the flow analysis is not possible.

As visible in both images, the spill still appears relatively confined around its point of origin and is still north of the Loop Current, a powerful <u>conveyor belt</u> that circulates clockwise around the Gulf toward Florida before being joining the powerful Gulf Stream.

An intriguing shape is detected in the 2 May image that seems to follow passively the flow derived from the Doppler measurements.





In this Envisat Advanced Synthetic Aperture Radar (ASAR) product for April 29, 2010, advanced processing methods have been performed to display ocean surface roughness variations and Doppler-derived ocean surface radial velocities around the oil spill area in the Gulf of Mexico. Smooth surfaces appear as black patches inside the oil spill and in the very low wind region east of the spill, where the flow analysis is not possible. As visible, the spill still appears relatively confined around its point of origin and is still north of the Loop Current. Credit: CLS

The fear is that winds could push the <u>oil slick</u> south until it joins the Loop Current, which would carry the oil towards Florida. If that were to happen, the oil could flow into the Gulf Stream and be carried up to the US East Coast.

"As observed, this does not seem to be the case at the moment as no



connection between the spill and the intense current presently occurs," said Dr Bertrand Chapron of IFREMER, the French Research Institute for Exploitation of the Sea. "Thanks to systematic Envisat ASAR planning over this area, close monitoring of the situation is ensured as long as there is some wind to contrast the surface roughness."

Dr Chapron and Dr Fabrice Collard of France's CLS (formerly the BOOST Technologies Company) created these products using ASAR in Wide Swath mode. They have been working with radar data for many years and have developed sets of algorithms that allow ASAR data to be processed in near-real time and to produce state-of-the-art ocean parameters. These are made widely available on the SOPRANO ocean products demonstration website developed with ESA.

"The upcoming Sentinel-1 SAR instrument will have an enhanced capability to capture the surface flow information on top of the higher resolution sea surface roughness," Dr Chapron explained. "As demonstrated, these combined products are very promising for strengthening the use of SAR data to help fight oil-spill consequences on coastal zones."

Sentinel-1 is a two-satellite system. The first Sentinel-1 satellite is planned for launch at the end 2012 and will ensure the continuity of SAR data. The second Sentinel-1 satellite is planned for launch in 2014. The fleet of Sentinel satellites is being developed by ESA within the EU's Global Monitoring for Environment and Security initiative.

Provided by European Space Agency

Citation: Envisat monitors oil spill proximity to Loop Current (2010, May 5) retrieved 3 May 2024 from <u>https://phys.org/news/2010-05-envisat-oil-proximity-loop-current.html</u>



This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.