


New 3-D photonic crystal has both electronic, optical properties

July 24 2011



Using an epitaxial approach, University of Illinois researchers developed a 3-D photonic crystal LED, the first such optoelectronic device. Credit: Erik Nelson

In an advance that could open new avenues for solar cells, lasers, metamaterials and more, researchers at the University of Illinois have demonstrated the first optoelectronically active 3-D photonic crystal.

"We've discovered a way to change the three-dimensional structure of a well-established <u>semiconductor material</u> to enable new optical properties while maintaining its very attractive <u>electrical properties</u>," said Paul Braun, a professor of materials science and engineering and of chemistry who led the research effort.

The team published its advance in the journal Nature Materials.



Photonic crystals are materials that can control or manipulate light in unexpected ways thanks to their unique physical structures. Photonic crystals can induce unusual phenomena and affect photon behavior in ways that traditional <u>optical materials</u> and devices can't. They are popular materials of study for applications in lasers, solar energy, LEDs, <u>metamaterials</u> and more.


However, previous attempts at making 3-D photonic crystals have resulted in devices that are only optically active that is, they can direct light but not electronically active, so they can't turn electricity to light or vice versa.

The Illinois team's photonic crystal has both properties.

"With our approach to fabricating photonic crystals, there's a lot of potential to optimize electronic and <u>optical properties</u> simultaneously," said Erik Nelson, a former graduate student in Braun's lab who now is a postdoctoral researcher at Harvard University. "It gives you the opportunity to control light in ways that are very unique to control the way it's emitted and absorbed or how it propagates."

To create a 3-D photonic crystal that is both electronically and optically active, the researchers started with a template of tiny spheres packed together. Then, they deposit gallium arsenide (GaAs), a widely used semiconductor, through the template, filling in the gaps between the spheres.





This graphic shows the method for epitaxial growth of 3-D photonic crystals. Credit: Erik Nelson

The GaAs grows as a single crystal from the bottom up, a process called epitaxy. Epitaxy is common in industry to create flat, two-dimensional films of single-crystal semiconductors, but Braun's group developed a way to apply it to an intricate three-dimensional structure.

"The key discovery here was that we grew single-crystal semiconductor through this complex template," said Braun, who also is affiliated with the Beckman Institute for Advanced Science and Technology and with the Frederick Seitz Materials Research Laboratory at Illinois. "Gallium arsenide wants to grow as a film on the substrate from the bottom up, but it runs into the template and goes around it. It's almost as though the template is filling up with water. As long as you keep growing GaAs, it keeps filling the template from the bottom up until you reach the top surface."

The epitaxial approach eliminates many of the defects introduced by top-down fabrication methods, a popular pathway for creating 3-D photonic structures. Another advantage is the ease of creating layered heterostructures. For example, a quantum well layer could be introduced into the photonic crystal by partially filling the template with GaAs and



then briefly switching the vapor stream to another material.

Once the template is full, the researchers remove the spheres, leaving a complex, porous 3-D structure of single-crystal semiconductor. Then they coat the entire structure with a very thin layer of a semiconductor with a wider bandgap to improve performance and prevent surface recombination.

To test their technique, the group built a 3-D photonic crystal LED the first such working device.

Now, Braun's group is working to optimize the structure for specific applications. The LED demonstrates that the concept produces functional devices, but by tweaking the structure or using other semiconductor materials, researchers can improve solar collection or target specific wavelengths for metamaterials applications or low-threshold lasers.

"From this point on, it's a matter of changing the device geometry to achieve whatever properties you want," Nelson said. It really opens up a whole new area of research into extremely efficient or novel energy devices.

More information: "Epitaxial Growth of Three-Dimensionally Architectured Optoelectronic Devices", *Nature Materials* (2011).

Provided by University of Illinois at Urbana-Champaign

Citation: New 3-D photonic crystal has both electronic, optical properties (2011, July 24) retrieved 18 April 2024 from

https://phys.org/news/2011-07-d-photonic-crystal-electronic-optical.html



This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.