

Improving the physics of grocery store display cases to save energy

October 13 2011



For his doctoral work at the University of Washington, Mazyar Amin used fluid dynamics to improve the energy efficiency of refrigerated grocery store display shelves. Here he stands beside the experimental setup at Michigan's Kettering University. Credit: Image courtesy of Kettering University

Shoppers don't usually give a second thought as they reach into a cooler to grab milk, cheese or prepackaged lunches. Open-front refrigerated display cases, which make up roughly 60 percent of the refrigerated

cases in grocery stores and supermarkets, provide quick access to chilled products such as dairy, meat, fish and produce. While they are popular with shoppers and grocery stores, they're less popular with electric utilities and others concerned with energy efficiency.

Engineers at the University of Washington and Kettering University are working to cut the amount of energy used by these coolers, while enhancing [product safety](#) and quality. Results published this month in the journal *Applied Thermal Engineering* show that tweaking the physics can reduce the energy used for refrigeration by as much as 15 percent. Lead author of the article is Mazyar Amin, a former UW doctoral student now doing postdoctoral research at Missouri's Saint Louis University.

Designing grocery display cases is not rocket science, but it has a lot in common with aeronautical engineering. Refrigerated display cases shoot jets of air across their front openings, creating an invisible shield that aims to keep cold air in and warm air out.

Current technology does this with limited success.

"Most of the energy these cases use goes into cooling infiltrated air," explains Dana Dabiri, a UW associate professor of aeronautics and astronautics. "Some energy goes to extract the heat from lighting and fan motors, some goes to remove the heat gain from radiation and [conduction](#), but 75 percent of the cooling load is attributed to infiltration of warm and moist air from the surrounding environment."

Open-air coolers are increasingly popular compared to other options. Refrigerated cases with doors are good at keeping cold air in, but they fog up when opened and can frustrate shoppers who want to look at more than one product while making a choice. Another design is to hang sheets of clear plastic in front of the opening, but some see this as tacky. Refrigerated bins that are open on top waste less energy because the cold

air is heavier, and tends to stay inside the case. The big energy hog, and the focus of the UW research, are open-air vertical shelves.



The experimental setup includes a half-scale display case shown in the lower left. Movable ducts adjust the settings for the air curtain that shoots across the opening. Credit: Image courtesy of Mazyar Amin

The team includes principal investigator Hodayun Navaz, a professor of mechanical engineering at Kettering who specializes in computational fluid dynamics and fluid flow simulations. Dabiri specializes in experimental work to measure and visualize fluid flows. Together they have directed five years of research in a cavernous lab on the Kettering campus in Flint, Mich.

There, researchers built a modular mock display case and an air curtain simulator to test various designs. They measured how much air was infiltrated for various air curtain speeds, angles, and other factors to minimize the amount of warm, moist air entering the chilled

compartment of the case.

"One approach is to ask, 'What are the optimal parameters so I can get the most efficient air curtain?' and then start building those," Dabiri said. "But instead of implementing costly redesigns for existing display cases, the question became, 'What minimal changes can I do to improve the [energy efficiency](#) of the existing units?'"

The new paper establishes key variables that strongly affect the amount of warm air penetrating the air curtain. Results show that the most important factors are the angle between the case's discharge and return air grilles, and jet's exit Reynolds number, a figure that depends on the air speed and density, and the jet's turbulence intensity.

Combining experimental results and mathematical models, the team developed a tool that lets manufacturers optimize their particular design. Researchers collaborated with a leading display-case manufacturer to retrofit a proof-of-concept case. Tests showed the retrofit was a cost-effective way to get a 10 percent reduction in infiltration of warm [air](#). (Calculations for other display designs show potential savings of up to 15 percent.)

Navaz's team has now established a company in Flint, Michigan, that provides technical tools and training to help display-case manufacturers improve their products' energy efficiency. "There's definitely room for improvement in these display cases," Dabiri said. "We've shown that we can get 10 to 15 percent improvement, which is definitely a tangible impact. In this whole push for [energy](#) efficiency, anything you can do is a help."

An industry-wide implementation of the findings across the U.S. would save roughly \$100 million in electricity costs each year.

Provided by University of Washington

Citation: Improving the physics of grocery store display cases to save energy (2011, October 13)
retrieved 20 April 2024 from <https://phys.org/news/2011-10-physics-grocery-cases-energy.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.