

Researchers build transparent, super-stretchy skin-like sensor (w/ video)

October 24 2011



A close-up view of the super-stretchy, transparent, highly sensitive skin-like sensor that Zhenan Bao, associate professor of chemical engineering, and Darren Lipomi, postdoctoral researcher in chemical engineering, developed at Stanford University with their colleagues. Credit: Steve Fyffe, Stanford News Service

Imagine having skin so supple you could stretch it out to more than twice its normal length in any direction - repeatedly - yet it would always snap back completely wrinkle-free when you let go of it. You would certainly never need Botox.

That enviable [elasticity](#) is one of several new features built into a new transparent skin-like [pressure sensor](#) that is the latest sensor developed by Stanford's Zhenan Bao, associate professor of chemical engineering, in her quest to create an artificial "super skin." The sensor uses a transparent film of single-walled carbon nanotubes that act as tiny springs, enabling the sensor to accurately measure the force on it,

whether it's being pulled like taffy or squeezed like a sponge.

"This sensor can register pressure ranging from a firm pinch between your thumb and forefinger to twice the pressure exerted by an elephant standing on one foot," said Darren Lipomi, a postdoctoral researcher in Bao's lab, who is part of the research team.

"None of it causes any permanent deformation," he said.

Lipomi and Michael Vosgueritchian, graduate student in chemical engineering, and Benjamin Tee, graduate student in electrical engineering, are the lead authors of a paper describing the sensor published online Oct. 23 by *Nature Nanotechnology*. Bao is a coauthor of the paper.

The sensors could be used in making touch-sensitive [prosthetic limbs](#) or robots, for various [medical applications](#) such as pressure-sensitive bandages or in touch screens on computers.

The key element of the new sensor is the transparent film of carbon "nano-springs," which is created by spraying nanotubes in a liquid suspension onto a [thin layer](#) of [silicone](#), which is then stretched.

When the nanotubes are airbrushed onto the silicone, they tend to land in randomly oriented little [clumps](#). When the silicone is stretched, some of the "nano-bundles" get pulled into alignment in the direction of the stretching.

When the silicone is released, it rebounds back to its original dimensions, but the nanotubes buckle and form little nanostructures that look like springs.

"After we have done this kind of pre-stretching to the nanotubes, they

behave like springs and can be stretched again and again, without any permanent change in shape," Bao said.

Stretching the nanotube-coated silicone a second time, in the direction perpendicular to the first direction, causes some of the other nanotube bundles to align in the second direction. That makes the sensor completely stretchable in all directions, with total rebounding afterward.

Additionally, after the initial stretching to produce the "nano-springs," repeated stretching below the length of the initial stretch does not change the electrical conductivity significantly, Bao said. Maintaining the same conductivity in both the stretched and unstretched forms is important because the sensors detect and measure the force being applied to them through these spring-like nanostructures, which serve as electrodes.

The [sensors](#) consist of two layers of the nanotube-coated silicone, oriented so that the coatings are face-to-face, with a layer of a more easily deformed type of silicone between them.

The middle layer of silicone stores electrical charge, much like a battery. When pressure is exerted on the sensor, the middle layer of silicone compresses, which alters the amount of electrical charge it can store. That change is detected by the two films of carbon nanotubes, which act like the positive and negative terminals on a typical automobile or flashlight battery.

The change sensed by the nanotube films is what enables the sensor to transmit what it is "feeling."

Whether the sensor is being compressed or extended, the two nanofilms are brought closer together, which seems like it might make it difficult to detect which type of deformation is happening. But Lipomi said it should be possible to detect the difference by the pattern of pressure.

With compression, you would expect to see sort of a bull's-eye pattern, with the greatest deformation at the center and decreasing deformation as you go farther from the center.

"If the device was gripped by two opposing pincers and stretched, the greatest deformation would be along the straight line between the two pincers," Lipomi said. Deformation would decrease as you moved farther away from the line.

Bao's research group previously created a sensor so sensitive to pressure that it could detect pressures "well below the pressure exerted by a 20 milligram bluebottle fly carcass" that the researchers tested it with. This latest sensor is not quite that sensitive, she said, but that is because the researchers were focused on making it stretchable and transparent.

"We did not spend very much time trying to optimize the sensitivity aspect on this sensor," Bao said.

"But the previous concept can be applied here. We just need to make some modifications to the surface of the electrode so that we can have that same sensitivity."

Provided by Stanford University

Citation: Researchers build transparent, super-stretchy skin-like sensor (w/ video) (2011, October 24) retrieved 23 April 2024 from <https://phys.org/news/2011-10-transparent-super-stretchy-skin-like-sensor-video.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.