

## New device could bring optical information processing

December 22 2011, by Emil Venere



This illustration shows a new "all-silicon passive optical diode," a device small enough to fit millions on a computer chip that could lead to faster, more powerful information processing and supercomputers. The device has been developed by Purdue University researchers. (Birck Nanotechnology Center, Purdue University)

(PhysOrg.com) -- Researchers have created a new type of optical device small enough to fit millions on a computer chip that could lead to faster, more powerful information processing and supercomputers.

The "passive optical diode" is made from two tiny silicon rings measuring 10 microns in diameter, or about one-tenth the width of a human hair. Unlike other optical <u>diodes</u>, it does not require external



assistance to transmit signals and can be readily integrated into computer chips.

The diode is capable of "nonreciprocal transmission," meaning it transmits signals in only one direction, making it capable of <u>information</u> <u>processing</u>, said Minghao Qi (pronounced Chee), an associate professor of electrical and computer engineering at Purdue University.

"This one-way transmission is the most fundamental part of a <u>logic</u> <u>circuit</u>, so our diodes open the door to optical information processing," said Qi, working with a team also led by Andrew Weiner, Purdue's Scifres Family Distinguished Professor of Electrical and Computer Engineering.

The diodes are described in a paper to be published online Thursday (Dec. 22) in the journal *Science*. The paper was written by graduate students Li Fan, Jian Wang, Leo Varghese, Hao Shen and Ben Niu, research associate Yi Xuan, and Weiner and Qi.

Although fiberoptic cables are instrumental in transmitting large quantities of data across oceans and continents, information processing is slowed and the data are susceptible to cyberattack when <u>optical signals</u> must be translated into <u>electronic signals</u> for use in computers, and vice versa.

"This translation requires expensive equipment," Wang said. "What you'd rather be able to do is plug the fiber directly into computers with no translation needed, and then you get a lot of bandwidth and security."

Electronic diodes constitute critical junctions in transistors and help enable <u>integrated circuits</u> to switch on and off and to process information. The new optical diodes are compatible with industry manufacturing processes for complementary metal-oxide-



semiconductors, or CMOS, used to produce <u>computer chips</u>, Fan said.

"These diodes are very compact, and they have other attributes that make them attractive as a potential component for future photonic information processing chips," she said.

The new optical diodes could make for faster and more secure information processing by eliminating the need for this translation. The devices, which are nearly ready for commercialization, also could lead to faster, more powerful supercomputers by using them to connect numerous processors together.

"The major factor limiting supercomputers today is the speed and bandwidth of communication between the individual superchips in the system," Varghese said. "Our optical diode may be a component in optical interconnect systems that could eliminate such a bottleneck."

Infrared light from a laser at telecommunication wavelength goes through an optical fiber and is guided by a microstructure called a waveguide. It then passes sequentially through two silicon rings and undergoes "nonlinear interaction" while inside the tiny rings. Depending on which ring the light enters first, it will either pass in the forward direction or be dissipated in the backward direction, making for one-way transmission. The rings can be tuned by heating them using a "microheater," which changes the wavelengths at which they transmit, making it possible to handle a broad frequency range.

**More information:** An All-Silicon Passive Optical Diode, *Science* (2011).

## ABSTRACT

A passive optical diode effect would be useful for on-chip optical information processing, but has been difficult to achieve. Based on



optical nonlinearity, we demonstrate a forward-backward transmission ratio up to 28 dB within telecommunication wavelengths using two 5-micrometer radius silicon rings. Our device is passive, yet maintains optical nonreciprocity for a broad range of input power levels and performs equally well even if the backward input power is higher than the forward input. The silicon optical diode is ultra compact and is compatible with current complementary metal-oxide-semiconductor (CMOS) processing.

Provided by Purdue University

Citation: New device could bring optical information processing (2011, December 22) retrieved 4 May 2024 from <u>https://phys.org/news/2011-12-device-optical.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.