

Portable gas sensors improve atmospheric pollution measurements

April 30 2012



Remote-controlled robotic helicopter in flight with a laser-based greenhouse gas sensor extending from its nose. The aerial detector is easy to deploy, inexpensive to operate, can be guided by GPS, and provides measurements in both vertical and horizontal directions. Credit: Department of Civil and Environmental Engineering, Princeton University

Different types of compact, low-power portable sensors under development by three independent research groups may soon yield unprecedented capabilities to monitor ozone, greenhouse gases, and air pollutants. The three teams will each present their work at the Conference on Lasers and Electro-Optics (CLEO: 2012), to be held May 6-11, in San Jose, Calif.

Princeton University engineer Amir Khan and colleagues, working with space scientists at the University of Texas at Dallas, will discuss how

their teams combined a compact, low-power, open-path (exposed directly to the environment) [laser sensor](#) with a [robotic helicopter](#) to measure the three most important [greenhouse gases](#) – carbon dioxide, methane and water vapor – in the atmosphere. The biggest advantage of the combination is that it provides high-resolution mapping in both the vertical and horizontal directions near emissions sources – something that ground-based networks or satellite-based sensors cannot do. Additionally, the sensor on the robotic helicopter is easy to deploy, inexpensive to operate, can be programmed to fly a preset monitoring pattern using GPS coordinates, and can handle challenging situations such as measuring emissions from industrial plants where the plumes move sideways as well as up.

A first-time demonstration of a system with the potential to become a portable, low-power, low-cost, and long-lasting optical sensor for [ozone](#) (O₃) measurements will be presented by a team of engineers from the University of Rostock in Germany and Sensor Electronic Technology Inc. in South Carolina. The sensor uses light-emitting diodes (LEDs) to produce light in the deep ultraviolet range of the spectrum (wavelengths less than 300 nanometers) that allows the detection of small amounts of ozone – trace concentrations ranging anywhere from approximately 10 parts per billion to approximately 100 parts per million. The team showed in tests that this sensitivity compares favorably to conventional sensors that use less durable and more expensive mercury or electrochemical light sources. The team also discovered that coupling the deep ultraviolet LED to the detection equipment with fiber-optic cables produced a sturdy sensor that could be used in harsh environments, such as areas with strong electromagnetic fields, high temperatures, or strong vibrations.

Finally, engineer David Miller, also from Princeton University, will discuss his team's use of an open-path quantum cascade [laser](#) to create a portable sensor that can detect extremely small quantities of atmospheric

ammonia (NH₃) in harsh field environments. This molecule commonly forms unhealthy particulate matter, but measurements of this pollutant in the atmosphere are lacking. The Princeton sensor has performed well when deployed in harsh environments – everything from dusty deserts to jungle-like conditions to sub-freezing temperatures – providing an ability to measure concentrations of NH₃ as small as 200 parts per trillion. Data from the high-sensitivity ammonia sensor will significantly improve air quality forecasts.

More information: <http://www%2Ccleoconference.org/>

Provided by Optical Society of America

Citation: Portable gas sensors improve atmospheric pollution measurements (2012, April 30)
retrieved 1 May 2024 from
<https://phys.org/news/2012-04-portable-gas-sensors-atmospheric-pollution.html>

<p>This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.</p>
--