

Stable electrodes for improving printed electronics

April 19 2012



After introducing what appears to be a universal technique to reduce the work function of a conductor in printable electronics, a team led by Georgia Tech's Bernard Kippelen has developed the first completely plastic solar cell. Credit: Virginie Drujon-Kippelen

Imagine owning a television with the thickness and weight of a sheet of paper. It will be possible, someday, thanks to the growing industry of printed electronics. The process, which allows manufacturers to literally print or roll materials onto surfaces to produce an electronically functional device, is already used in organic solar cells and organic light-emitting diodes (OLEDs) that form the displays of cellphones.

Although this [emerging technology](#) is expected to grow by tens of billions of dollars over the next 10 years, one challenge is in

manufacturing at low cost in [ambient conditions](#). In order to create light or energy by injecting or collecting electrons, printed electronics require conductors, usually calcium, magnesium or lithium, with a low-work function. These metals are chemically very reactive. They oxidize and stop working if exposed to oxygen and moisture. This is why electronics in solar cells and TVs, for example, must be covered with a rigid, thick barrier such as glass or expensive encapsulation layers.

However, in new findings published in the journal *Science*, Georgia Tech researchers have introduced what appears to be a universal technique to reduce the work function of a conductor. They spread a very [thin layer](#) of a polymer, approximately one to 10 [nanometers](#) thick, on the conductor's surface to create a strong surface dipole. The interaction turns air-stable conductors into efficient, low-work function electrodes.

The commercially available polymers can be easily processed from dilute solutions in solvents such as water and methoxyethanol.

"These polymers are inexpensive, environmentally friendly and compatible with existent roll-to-roll mass production techniques," said Bernard Kippelen, director of Georgia Tech's Center for Organic Photonics and Electronics (COPE). "Replacing the reactive metals with stable conductors, including [conducting polymers](#), completely changes the requirements of how electronics are manufactured and protected. Their use can pave the way for lower cost and more flexible devices."

To illustrate the new method, Kippelen and his peers evaluated the polymers' performance in organic thin-film transistors and OLEDs. They've also built a prototype: the first-ever, completely plastic solar cell.

"The polymer modifier reduces the work function in a wide range of conductors, including silver, gold and aluminum," noted Seth Marder,

associate director of COPE and professor in the School of Chemistry and Biochemistry. "The process is also effective in transparent metal-oxides and graphene."

Provided by Georgia Institute of Technology

Citation: Stable electrodes for improving printed electronics (2012, April 19) retrieved 26 April 2024 from <https://phys.org/news/2012-04-stable-electrodes-electronics.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.