

Glass offers improved means of storing UK's nuclear waste

August 22 2012

University of Sheffield researchers have shown, for the first time, that a method of storing nuclear waste normally used only for high level waste, could provide a safer, more efficient, and potentially cheaper, solution for the storage and ultimate disposal of intermediate level waste.

ILW makes up more than three quarters of the volume of material destined for geological disposal in the UK. (1)

Currently the UK's preferred method is to encapsulate ILW in specially formulated cement. The [waste](#) is mixed with cement and sealed in steel drums, in preparation for disposal deep underground.

Two studies, published in the latest issues of *The Journal of [Nuclear Materials](#)* and *European Journal of [Glass Science and Technology A](#)* show that turning this kind of waste into glass, a process called vitrification, could be a better method for its long-term storage, transport and eventual disposal.

HLW is already processed using this technology which reduces both the [reactivity](#) and the volume of the waste produced. Until now, this method has not been considered suitable for ILW because the technology was not developed to handle large quantities of waste composed from a variety of different materials.

The research programme, funded by the UK's NDA and led by Professor Neil Hyatt in the Department of [Materials Science and Engineering](#), at

the University of Sheffield, tested simulated radioactive [waste materials](#) – those with the same chemical and physical makeup, but with non-radioactive isotopes – to produce glass and assess its suitability for storing lower grades of [nuclear waste](#).

The process used to produce the glass waste storage packages is straightforward: the waste is dried, mixed with glass forming materials such as iron oxide or sodium carbonate, heated to make glass and finally poured into a container. For certain wastes – for example radioactively contaminated sand – the waste is actually used in the glass-making process.

A key discovery made by the Sheffield team was that the glasses produced for ILW proved to be very resistant to damage by energetic gamma rays, produced from the decay of radioactive materials. "We found that gamma irradiation produced no change in the physical properties of these glasses, and no evidence that the residual radiation caused defects," says Professor Hyatt. "We think this is due to the presence of iron in the glass, which helps heal any defects so they cannot damage the material."

"For large volumes of waste that need to be stored securely, then transported to and eventually disposed of, vitrification could offer improved safety and cost effectiveness" explains Professor Hyatt.

Dr Darrell Morris, Research Manager, NDA said "We welcome this fundamental research demonstrating a possible alternative means of treating ILW. We look forward to seeing further progress on the applicability of this technology to the UK's waste inventory"

More information: (1) Radioactive Waste in the UK: The 2010 Estimate of Radioactive Waste for Geological Disposal

Provided by University of Sheffield

Citation: Glass offers improved means of storing UK's nuclear waste (2012, August 22) retrieved 26 April 2024 from <https://phys.org/news/2012-08-glass-uk-nuclear.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.