

Bottom-up approach provides first characterization of pyroelectric nanomaterials

January 8 2013

By taking a "bottom-up" approach, researchers at the University of Illinois at Urbana-Champaign have observed for the first time that "size does matter" in regards "pyroelectricity"—the current/voltage developed in response to temperature fluctuations that enables technologies such as infrared sensors, night-vision, and energy conversion units, to name a few.

"Controlling and manipulating heat for applications such as waste [heat energy](#) harvesting, integrated cooling technologies, [electron emission](#), and related functions is an exciting field of study today," explained Lane Martin, an assistant professor of [materials science and engineering](#) at Illinois. "Traditionally, these systems have relied on bulk materials, but future [nanoscale devices](#) will increasingly require ferroelectric thin films.

"Measuring the pyroelectric response of thin films is difficult and has restricted the understanding of the physics of pyroelectricity, prompting some to label it as 'one of the least-known properties of [solid materials](#)'," Martin added. "This work provides the most complete and detailed modeling and experimental study of this widely unknown region of materials and has direct implications for next generation devices."

Researchers found that reducing the dimensions of ferroelectrics increases their susceptibility to size- and strain-induced effects. The

group's paper, "Effect of 90-degree domain walls and thermal expansion mismatch on the pyroelectric properties of epitaxial $\text{PbZr}_{0.2}\text{Ti}_{0.8}\text{O}_3$ thin films," appears in the journal [Physical Review Letters](#).

"What we did in this work was to develop a new approach to utilize and understand a class of materials important for all of these applications," Martin said. "By moving to a 'bottom-up' approach that produces nanoscale versions of these materials as thin films, we have observed, for the first time, that certain features, namely domain walls, can be incredibly important and even dominate the temperature-dependent response and performance of these materials."

According to J. Karthik, the first author on the group's paper, thin-film epitaxy has been developed to provide a set of parameters (e.g., film composition, epitaxial strain, electrical boundary conditions, and thickness) that allow for precise control of [ferroelectrics](#) and has been instrumental in understanding the physics of dielectric and piezoelectric effects.

"We investigated the contribution of 90° domain walls and thermal expansion mismatch to pyroelectricity in ferroelectric $\text{PbZr}_{0.2}\text{Ti}_{0.8}\text{O}_3$ thin films, a widely used material whose bulk ferroelectric and piezoelectric properties are well understood," Karthik explained. As part of this work, Martin's Prometheus research group developed and applied the first phenomenological models to include extrinsic and secondary contributions to pyroelectricity in polydomain films and predict significant extrinsic contributions (arising from the temperature-dependent motion of domain walls) and large secondary contributions (arising from thermal expansion mismatch between the film and the substrate).

"We have also developed and applied a new phase-sensitive pyroelectric current measurement process to measure thin films for the first time and

reveal a dramatic increase in the pyroelectric coefficient with increasing fraction of in-plane oriented domains and thermal expansion mismatch consistent with these models," Karthik said.

"By establishing an understanding of the science of these effects, with models to predict their performance, and demonstrated techniques to fabricate and utilize these properties in nanoscale versions of these materials, their properties can be effectively integrated into existing electronics," Martin said.

Provided by University of Illinois at Urbana-Champaign

Citation: Bottom-up approach provides first characterization of pyroelectric nanomaterials (2013, January 8) retrieved 1 May 2024 from <https://phys.org/news/2013-01-bottom-up-approach-characterization-pyroelectric-nanomaterials.html>

<p>This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.</p>
--