

# The wireless way to safer sub-station

April 3 2013

---

New Professor of Radio Science and Wireless Systems Engineering at the University of Huddersfield heads a £670,000 project to find a more effective and efficient means of fault detection - meaning few blackouts and better safety standards

A £670,000 research project headed by a new University of Huddersfield professor promises major [economic benefits](#), higher [safety standards](#) and less likelihood of [power](#) cuts by transforming the techniques for detecting potentially dangerous and destructive faults in electricity sub-stations.

Ian Glover has been appointed Professor of Radio Science and Wireless Systems Engineering and a key area of his research is the use of easily-installed wireless sensor networks in sub-stations. This technology is designed to locate and diagnose imminent system faults, so that repairs can be made.

Professor Glover explains that when the insulation of cables and other power equipment becomes old or damaged, it radiates microwave energy, known as partial discharge.

"This can be picked up by radio receivers and by monitoring the intensity of this [microwave energy](#), you can predict when an item of plant is going to fail."

Traditionally, partial discharge has usually been detected by a technician walking the substation with a [radio receiver](#) and a pair of headphones.

"He listens to an audio signal that simply gives some basic information about whether partial discharge is present or not and with a bit of luck, the closer he is to the partial discharge the more intense it sounds," said Professor Glover.

"That might typically be only done once a year, but that is not enough. A piece of equipment can degrade very quickly."

In the worst cases, equipment can explode, leading to power cuts and massive repair costs plus safety risks – although modern sub-stations in the UK are not generally manned.

Professor Glover is the lead investigator on the £670,000 project, funded by the Engineering and Physical Sciences Research Council (EPSRC), which will develop the principle of [wireless sensor networks](#), which can be monitored centrally.

"You get a quicker diagnosis and it means that you can move from planned maintenance to condition-based maintenance," explained Professor Glover. "You don't have to maintain everything quite so often if its health is being measured all the time. You can wait until something is about to go wrong."

This would produce efficiency savings, cut down on the cost of equipment replacement and avoid the large fines levied on utility companies in the wake of power cuts.

The novel feature of Professor Glover's EPSRC-funded research is that he would use free space radiometers to sense microwave radiation intensity. These instruments are not attached to the power cables and can be installed without switching high voltage equipment off, so there is no interruption to power supplies.

"They can be reconfigured and installed very quickly and very conveniently and do not require demanding time synchronisation."

Provided by University of Huddersfield

Citation: The wireless way to safer sub-station (2013, April 3) retrieved 19 April 2024 from <https://phys.org/news/2013-04-wireless-safer-sub-station.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.