

New manufacturing method to help automakers lighten up

July 19 2013

New federal fuel-efficiency rules are forcing auto makers to lighten up their vehicles – a task that has proved difficult given the challenge of combining high-strength steels with lighter metals.

But a new method from BYU's School of Technology may be helpful to automakers in achieving the 54.5 miles per gallon average the EPA is mandating for U.S. fleets by 2025.

Manufacturing engineering technology professor Michael Miles has found a way to successfully create an extremely strong bond between lightweight aluminum and ultra-high-strength steel. It's called friction bit joining, and it may be the breakthrough the <u>automotive industry</u> is looking for.

"It's all about making vehicles lighter and our process can help to combine steels and light metals in the same vehicle frame, which gives engineers more flexibility in designing an optimal structure," Miles said.

The process of friction bit joining uses a small, consumable bit to create a solid-state joint between metals. The method was invented by Miles and retired BYU professor Kent Kohkonen, in their collaboration with local Orem-based company MegaStir Technologies.

The latest development in the process successfully bonds lightweight aluminum with cast iron by inserting a thin layer of steel between the two metals, which facilitates the bonding process. Findings of this



research, carried out in collaboration with the University of Ulsan in South Korea, are published in the June issue of the International Journal of Precision Engineering and Manufacturing.

"The motivation to make cars lighter was already there with a previous EPA mandate (34.5 mpg by 2016), but that motivation has now increased with the latest mandate," Miles said. "Our process is a technical success in the effort to spot join dissimilar metals together; now we need to go forward with our partners to make it commercially viable."

Currently, the automotive industry uses resistance spot welding to join steel stampings together into a completed body. In recent years, some aluminum parts have been introduced into the vehicle structure using a mechanical fastening method called self-piercing riveting. While this approach works to join lower strength steels with aluminum, it isn't suitable for joining aluminum to ultra-high-strength steel.

BYU's friction bit joining method, which is being developed in collaboration with MegaStir and Oak Ridge National Lab, has received funding from the National Science Foundation, the Department of Energy, the state of Utah and some auto suppliers in South Korea.

Applications for the process include areas of the vehicle frame where ultra-high-strength steel needs to be joined to a light metal.

For example, an automaker may want to use aluminum for the roof of a car while using ultra-high-strength steel for the A and B pillars of the frame that connect with the roof. Another example includes the incorporation of lighter weight metals on the interior parts of the car door.

Miles said the ability of friction bit joining to produce "incredible



strength between two dissimilar metals" will eventually benefit both automakers and other industries, like aerospace.

"It's great to be working on a project that's making a difference," said Lile Squires, a manufacturing systems graduate student working with Miles. "We know this process could be used in a lot of places."

Provided by Brigham Young University

Citation: New manufacturing method to help automakers lighten up (2013, July 19) retrieved 26 June 2024 from <u>https://phys.org/news/2013-07-method-automakers.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.