

Mathematical model controls a micromanipulation system more accurately

January 14 2015



A capacitance gauge (top left) measures the accuracy of a micromanipulator system (bottom right), which is controlled by an enhanced analytic forward model. Credit: A*STAR Institute for Infocomm Research

A mathematical model can improve the accuracy and repeatability of a positioning system by learning to anticipate tiny errors in its movements, show A*STAR researchers.

Micromanipulation systems are used to control objects' positions with exquisite precision and play a vital role in applications such as telescopes and <u>laser communication</u>. Most rely on feedback sensors to reach the desired position, but these sensors introduce a time lag that can reduce the accuracy in applications requiring rapid responses. Although analytic forward models (AFMs) can be used to predict when positioning <u>errors</u>



might occur and compensate for them in advance, they must be extremely accurate and uniquely tailored to a particular micromanipulation system.

Now, Yan Wu of the A*STAR Institute for Infocomm Research in Singapore, in collaboration with colleagues from the Harbin Institute of Technology in China, has developed a system that combines both approaches. The team created a machine learning algorithm that can improve the accuracy of its analytic control model based on sensor feedback.

Their enhanced analytic forward model (EAFM) combines a simple AFM with a 'heteroscedastic Gaussian process (HGP) algorithm, which compensates for any residual difference between the AFM's output and the desired position.

The team built a tip-tilt micromanipulation system that uses four piezoelectric drivers to change the position of its platform. These drivers can move the platform up to 32 micrometers, and position it with an accuracy of 10 nanometers. A capacitance gauge located next to the platform can measure its position to within one nanometer (see image).





Yan Wu from the A*STAR Institute of Infocomm Research in Singapore. Credit: A*STAR Institute for Infocomm Research

The researchers trained the HGP algorithm by running 125 random control signals through their micromanipulation system. It learned to make probabilistic predications that could compensate for errors in the AFM's output.

The team then tested the system with 30 different control signals, which were intended to move the platform by up to 28 micrometers. In every case, the EAFM system achieved smaller positioning errors than the AFM alone. And in trials of continuous movement, where the platform



had to hit a series of four different points over a brief time, the EAFM outperformed the AFM in all but one of ten tests.

"All the experiments demonstrated that the AFM has errors with a very large variance (between 1 and 8 micrometers), whereas the EAFM keeps the errors at around 1 micrometer or less," says Wu. "We are now putting this micromanipulator <u>platform</u> into a laser communication system, while investigating methods to further reduce the steady-state errors."

More information: Su, Y., Dong, W., Wu, Y., Du, Z. & Demiris, Y. Increasing the accuracy and the repeatability of position control for micromanipulations using heteroscedastic Gaussian processes. 2014 *IEEE International Conference on Robotics and Automation (ICRA)*, 4692–4698 (2014). dx.doi.org/10.1109/ICRA.2014.6907545

Provided by Agency for Science, Technology and Research (A*STAR), Singapore

Citation: Mathematical model controls a micromanipulation system more accurately (2015, January 14) retrieved 28 June 2024 from <u>https://phys.org/news/2015-01-mathematical-micromanipulation-accurately.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.