

Heating with the sun

August 3 2015



Solar-Active-Houses get most of their heat from the sun. Researchers carried out scientific tests to explore how this energy concept can be optimized further.

Credit: Fraunhofer ISE

Solar-Active-Houses heat themselves using heat collectors and water tanks. However, no one had conducted an objective assessment of how efficiently they do so. Fraunhofer researchers put some of these solar

houses to the test, identified where there was room for improvement and laid the scientific groundwork for this housing concept.

Most of us know how irritating it is to pay for domestic hot water and space heating and then find out at the end of the year that you still owe. This wouldn't happen to you if you lived in one of the 1700 solar houses dotted around Germany, Switzerland and Austria. These houses are heated primarily using solar energy: Solar thermal collectors on the roof are used to heat water, which is stored in a large tank and used later for heating the house and providing hot water. Since these houses have excellent insulation, that takes care of some 60 percent of their heat demand.

Solar-Active-Houses are ideal for achieving the European Union's Energy Performance of Buildings Directive, which stipulates that all buildings built from 2021 onwards have to be nearly zero-energy buildings – in other words, buildings that consume minimum amounts of fuel. Solar houses are a viable alternative to passive houses, which rely chiefly on very strong insulation and a ventilation system that recovers and redistributes heat. Solar-Active-Houses have, however, been struggling to overcome one flaw – they hadn't undergone any systematic scientific testing or objective assessments of their efficiency.

Nine solar houses scientifically monitored

It is this scientific groundwork that has now been completed as part of the "Heizsolar" project, conducted by researchers from the Fraunhofer Institute for Solar Energy Systems ISE in Freiburg, Germany, together with colleagues at Solar- und Wärmetechnik Stuttgart, the Technische Universität Ilmenau and the Sonnenhaus-Institut. "For Heizsolar, we monitored nine Solar-Active-Houses over multiple heating periods," says Gerhard Stryi-Hipp, group manager at Fraunhofer ISE. "This gave us a foundation from which to optimize the houses and lower costs. We

expect this will significantly enhance their importance in the future." The project was supported by the Forschungszentrum Jülich and received 1.5 million euros in funding from the German Federal Ministries for the Environment, Nature Conservation, Building and Nuclear Safety, and for Economic Affairs and Energy.

So what options do Solar-Active-Houses offer? In theory, it's possible to tap enough [solar energy](#) to cover a building's entire heating needs. But 100-percent solar houses are still something of a rarity – they are expensive and require that a significant amount of space be given over to the necessary long-term heat storage unit, which can sometimes be large enough to hold up to 50,000 liters. "Solar-Active-Houses which generate around 60 percent of the heat required using [solar thermal collectors](#) are a good and affordable compromise," Stryi-Hipp explains. "During spring and fall, 40 square meters of solar thermal collectors and a 5000-liter tank are fully sufficient for a single-family home. From November through January, the additional 40 percent must come from a gas or wood-fired boiler."

Up to now, the design of solar houses has relied mainly on the practical experience of individual experts. The researchers therefore decided to explore how to further optimize the Solar-Active-House and came up with a suitable simulation model to examine various aspects. For example, to what extent can the size of the tank be reduced in order to increase these houses' popularity? "It's possible to vary the ratio of tank size to collector surface area: In our 60-percent Solar-Active-House, we found we could reduce the tank volume from 6000 to 3000 liters as long as we also increased the area of solar heat collectors from 40 to 60 square meters."

Solar houses still have their share of challenges to overcome. The researchers have concluded that several of these challenges can be easily solved with thorough planning. Take the heat emitted by the storage

tank, for example. While this is welcome in winter, in summer no one wants to further heat up an already warm house. "If you install the tank in the stairwell, for instance, the waste heat isn't wasted during heating season. And if you also install a window through which waste heat can be released, it won't bother you in the summer," says Stryi-Hipp. Other challenges call for further research, including how Solar-Active-Houses stack up against zero-energy or plus-energy houses. These are equipped with photovoltaic elements to generate electricity that is used in part to power [heat](#) pumps. The researchers plan to address this topic as part of a follow-up project so they can provide users with reliable assessment criteria.

Provided by Fraunhofer-Gesellschaft

Citation: Heating with the sun (2015, August 3) retrieved 3 May 2024 from <https://phys.org/news/2015-08-sun.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.