

## New tool can nondestructively characterize structural materials in unprecedented detail as they deform

September 8 2015





This setup is used for high-energy diffraction microscopy experiments -- it involves a rotational and axial motion system load frame insert in a conventional load frame along with near-field and far-field detectors. The loading axis is vertical, and the specimen and specimen grips rotate around the loading axis while the rest of the setup remains stationary. Credit: Review of Scientific Instruments

Materials scientists are busy developing advanced materials, while also working to squeeze every bit of performance out of existing materials. This is particularly true in the aerospace industry, where small advantages in weight or extreme temperature tolerance quickly translate into tremendous performance benefits.

The potential pay-offs motivated a team of researchers from the Air Force Research Laboratory, the Advanced Photon Source, Lawrence Livermore National Laboratory, Carnegie Mellon University and PulseRay to work together to pursue their shared goal of characterizing structural <u>materials</u> in unprecedented detail.

In a paper in *Review of Scientific Instruments*, from AIP Publishing, the group describes how they created a system to squeeze and stretch a material while at the same time rotating and bombarding it with highenergy synchrotron X-rays. The X-rays capture information about how the material responds to the mechanical stress.

"This required developing a loading system to enable the precise rotation of a sample while simultaneously and independently applying tensile or compressive axial loading," explained Paul A. Shade, lead author and a materials research engineer for the Air Force Research Laboratory at



Wright-Patterson Air Force Base.

Their approach included "developing and validating micromechanical models to help us understand the sources of failure in materials so that we can produce aerospace components that are lighter and more damage tolerant—while also gaining a more complete understanding of their service lifetime capability," Shade added.

The main significance of the team's new tool is that "the RAMS load frame insert enables applying axial loads while the specimen is continuously rotated, which means that we can integrate near-field and far-field high-energy diffraction microscopy methods and microtomography with in situ mechanical testing," said Shade. "This allows us to nondestructively characterize the microstructure and micromechanical state of a deforming material—providing critical validation data for microstructure-sensitive performance-prediction models."

The materials community is interested in using the team's tool as part of an integrated computational materials engineering approach to design structural components—which could help optimize materials properties and reduce uncertainty for given applications. The measurements that this tool enables can be used to develop new materials for turbine engines, car parts and industrial machinery, to name just a few applications.

"An important aspect is to develop trusted materials models whose performance has been validated at the appropriate length scale," Shade said.

The next step for the team will be partnering with researchers at the Cornell High Energy Synchronous Source (CHESS), Cornell University and the Advanced Photon Source (APS) at Argonne National Laboratory



to develop standalone RAMS load frames. "These instruments will be made available to the high-energy synchrotron X-ray community and, in fact, have already been used by many researchers and institutions," Shade noted.

The team is currently working with CHESS and APS to develop elevated temperature and multi-axial loading capabilities. The RAMS load frame insert has also inspired the development of a tension in-vacuum furnace design for studying irradiated materials at APS that was developed in concert with the Nuclear Engineering Division at Argonne National Laboratory.

"We plan to host the datasets we collect from these experiments for others in the community to use—especially to test new materials models," Shade said. "In this manner, we'll help propel the community to develop microstructure-sensitive materials models and provide the validation needed to push materials to the next level of performance."

**More information:** "A rotational and axial motion system load frame insert for in situ high- energy x-ray studies," by Paul A. Shade, Basil Blank, Jay C. Schuren, Todd J. Turner, Peter Kenesei, Kurt Goetze, Robert M. Suter, Joel V. Bernier, Shiu Fai Li, Jonathan Lind, Ulrich Lienert and Jonathan Almer, *Review of Scientific Instruments*, September 8, 2015. <u>scitation.aip.org/content/aip/ ... /8/10.1063/1.4927855</u>

## Provided by American Institute of Physics

Citation: New tool can nondestructively characterize structural materials in unprecedented detail as they deform (2015, September 8) retrieved 17 May 2024 from <a href="https://phys.org/news/2015-09-tool-nondestructively-characterize-materials-unprecedented.html">https://phys.org/news/2015-09-tool-nondestructively-characterize-materials-unprecedented.html</a>



This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.