

Dielectric film has refractive index close to air

October 12 2015



By manipulating the structure of aluminum oxide, a dielectric material, researchers were able to improve its optical and mechanical properties. The key to the film's performance is the highly-ordered spacing of the pores, which gives it a more mechanically robust structure without impairing the refractive index. You can see the structure here, on the micrometer scale. Credit: Chih-Hao Chang

Researchers from North Carolina State University have developed a dielectric film that has optical and electrical properties similar to air, but is strong enough to be incorporated into electronic and photonic devices - making them both more efficient and more mechanically stable.



At issue is something called refractive index, which measures how much light bends when it moves through a substance. Air, for example, has a refractive index of 1, while water has a refractive index of 1.33 - which is why a straw appears to bend when you put it in a glass of water.

Photonic devices require a high contrast between its component materials, with some components having a high refractive index and others have a low one. The higher the contrast between those materials, the more efficient the photonic device is - and the better it performs. Air has the lowest refractive index, but it isn't mechanically stable. And the lowest refractive index found in solid, naturally occurring materials is 1.39.

But now researchers have developed a film made of <u>aluminum oxide</u> that has a refractive index as low as 1.025 but that is mechanically stiff.

"By manipulating the structure of the aluminum oxide, which is dielectric, we've improved both its optical and mechanical properties," says Chih-Hao Chang, corresponding author of a paper on the work and an assistant professor of mechanical and aerospace engineering at NC State. Dielectrics are insulator materials that are used in an enormous array of consumer products. For example, every handheld device has hundreds of capacitors, which are dielectric components that can store and manage electric charge.

"The key to the film's performance is the highly-ordered spacing of the pores, which gives it a more mechanically robust structure without impairing the refractive index," says Xu Zhang, lead author of the paper and a Ph.D. student at NC State.

The researchers make the film by first using a nanolithography developed in Chang's lab to create highly-ordered pores in a polymer substrate. That porous polymer then serves as a template, which the



researchers coats with a thin layer of aluminum oxide using <u>atomic layer</u> <u>deposition</u>. The polymer is then burned off, leaving behind a threedimensional aluminum oxide coating.

"We are able to control the thickness of the aluminum oxide, creating a coating between two nanometers and 20 nanometers thick," Zhang says. "Using <u>zinc oxide</u> in the same process, we can create a thicker coating. And the thickness of the coating controls and allows us to design the <u>refractive index</u> of the film." Regardless of the how thick the coating is, the film itself is approximately one micrometer thick.

"The steps in the process are potentially scalable, and are compatible with existing chip manufacturing processes," Chang says. "Our next steps include integrating these materials into functional optical and electronic devices."

More information: The paper, "Ordered Three-Dimensional Thin-Shell Nanolattice Materials with Near-Unity Refractive Indices," is published online in the journal *Advanced Functional Materials*. <u>onlinelibrary.wiley.com/doi/10 ... m.201502854/abstract</u>

Provided by North Carolina State University

Citation: Dielectric film has refractive index close to air (2015, October 12) retrieved 10 May 2024 from <u>https://phys.org/news/2015-10-dielectric-refractive-index-air.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.