

Characterization of soft magnetic nanocomposites

December 10 2015

Optimizing the performance of soft magnetic materials requires an understanding of the nanostructure and consideration of the local composition of each phase. The researchers successfully correlated the crystallization state in the alloy to local composition with novel mass balance. The alloy of composition $(\text{Fe}_{65}\text{Co}_{35})_{79.5}\text{B}_{13}\text{Si}_2\text{Nb}_4\text{Cu}_{1.5}$ was synthesized and subsequently heat-treated by the research group of Professor Michael McHenry of Carnegie Mellon University. Atom probe tomography (APT) was then used to characterize the various stages of crystallization in EMSL, the Environmental Molecular Sciences Laboratory. APT produced 3-D atom maps of all alloy constituents (shown in the IEEE Transactions on Magnetics cover). The local concentrations of elements obtained through APT were then used in mass balances (quantifying the glass formers in nanocrystals, enrichment of glass formers, and depletion of iron and cobalt in the amorphous phase).

Soft [magnetic materials](#) do not retain their magnetism when removed from a magnetic field and are widely used to construct magnetic components for motors, power generators, and power electronics. "Soft" refers to their small coercivity, meaning they can be easily magnetized or demagnetized. The challenge is to develop scalable routes for producing bulk quantities of soft magnetic material while retaining the unique nanoscale features responsible for the desirable soft magnetic properties.

Improving the performance of bulk soft magnetic materials can make a large impact in power conversion and electric machines alone because

30 percent of electricity consumed in the United States is used by electric motors, and 80 percent of all generated electricity is projected to flow through power electronics by 2030. High-performance soft magnetic materials can greatly improve the efficiency of electricity generation. For example, a 1 percent increase in energy generation efficiency through advanced soft magnetic materials can result in 159 TWh in energy savings.

A goal of the MS³ Initiative is to develop methods to produce bulk nanostructured materials using scalable, cost-effective processes based on an understanding of the scientific principles underlying those processes. PNNL is using novel processing techniques to produce bulk nanostructured materials with nanometer-sized features for use in [power electronics](#) (soft magnets), waste energy harvesting (thermoelectric), and lightweight cars/trucks (structural materials). These techniques could revolutionize our ability to make advanced, high-performance materials.

More information: Vincent DeGeorge et al. Mass Balance and Atom Probe Tomography Characterization of Soft Magnetic (Fe₆₅Co₆₅)_{79.5}B₁₃Si₂Nb₄Cu_{1.5} Nanocomposites, *IEEE Transactions on Magnetics* (2015). [DOI: 10.1109/TMAG.2014.2373333](https://doi.org/10.1109/TMAG.2014.2373333)

Provided by Pacific Northwest National Laboratory

Citation: Characterization of soft magnetic nanocomposites (2015, December 10) retrieved 4 August 2024 from <https://phys.org/news/2015-12-characterization-soft-magnetic-nanocomposites.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.