


Watering solar cells makes them grow... in power

July 27 2016, by Michele Fontana



Perovskite solar cells. Credit: OIST


Perovskite solar cells are the rising star in the photovoltaic landscape. Since their invention, less than ten years ago, their efficiency has doubled twice and it is now over 22% - an astonishing result in the renewable energy sector. Taking the name 'perovskite' from the light-harvesting layer that characterizes them, these solar cells are lighter, cheaper, and more flexible than the traditional crystalline silicon-based cells.

Perovskite [solar cells](#) are usually exposed to [ambient air](#) for several hours after fabrication. This procedure increases their [efficiency](#), even if the reason behind the phenomenon was unclear. The scientific explanation of this practice has now been discovered by researchers from the Energy Materials and Surface Sciences Unit (EMSS) at the

Okinawa Institute of Science and Technology Graduate University (OIST) led by Prof Yabing Qi. Their results are published in *Advanced Materials Interfaces*.

"It's intriguing: why do we need ambient air to enhance the effectiveness of [perovskite solar cells](#)?" Zafer Hawash, first author of the study and an OIST PhD student, commented. "Which component of the ambient air is linked to this phenomenon?" Starting from these questions, the researchers focused their attention on the top layer of the solar cells.

The choice was logical, because even if perovskite solar cell contains several layers - all of which may play a role in the cell efficiency - the top-most layer is the one in direct contact with ambient air. Thus, that is the layer most likely affected by the external environment. The layer is called 'hole transport layer', and it has a dopant, which is a substance that enhances the electrical conductivity of the material. "It is known that the dopant of the hole transport layer plays a key role in perovskite solar cells' performance," Hawash said. "But it was not clear how."



Mr. Zafer Hawash setting up the hanging mercury drop electrode system for conductivity measurement. Credit: OIST


The scientists performed controlled exposure of the hole transport layer to environmental gasses, focusing on oxygen, nitrogen, and moisture - water that is in a gas state. Then, they checked the electrical properties of the hole transport layer, using a variety of methods, to see if and how the inside of the transport layer changed. "What we found is that oxygen and nitrogen do not have any role in the redistribution of the dopants," Hawash explained. "But in the case of moisture, the solar cells' efficiency increases. This is the discovery: moisture is the air component that causes the redistribution of the dopant across the material, and thus the enhancement of the electric properties of the solar cells."

The scientists explain this phenomenon with the structure of the transport layer, which has many pinholes that allow the passage of gasses between the ambient and the underneath material. The dopant in the transport layer is a salt - Lithium TFSI. Being a salt, the dopant has a hygroscopic nature: it absorbs water. When the solar cells are exposed to moisture, the water absorbed by the transport layer causes the dopant to redistribute. However, long time exposure to moisture has a detrimental effect on the solar cells.

During their experiments, the researchers were also able to document the role of oxygen in the solar cells' performance. "Oxygen enhances the electrical conductivity of the transport layer as well, but this effect does not last long," Hawash commented. "But with the right amount of exposure to moisture, the electric proprieties are irreversibly enhanced."

Exposing the device to moisture after fabrication is then the most effective way to enhance the solar cells' performance.

Counterintuitively, then, water is what you need to have a perovskite solar cell that works properly. This finding is of high importance for the perovskite solar cells' future, as it finally explains a common practice whose effectiveness was mostly anecdotic, and thus could now lead the way to further improvement in the perovskite solar cells' performance.



(From left) Professor Yabing Qi, Mr. Zafer Hawash, and Dr. Luis K. Ono, from the OIST Energy Materials and Surface Sciences Unit. Credit: OIST

More information: Zafer Hawash et al, Moisture and Oxygen Enhance Conductivity of LiTFSI-Doped Spiro-MeOTAD Hole Transport Layer in Perovskite Solar Cells, *Advanced Materials Interfaces* (2016). [DOI: 10.1002/admi.201600117](https://doi.org/10.1002/admi.201600117)

Provided by Okinawa Institute of Science and Technology

Citation: Watering solar cells makes them grow... in power (2016, July 27) retrieved 10 April 2024 from <https://phys.org/news/2016-07-solar-cells-power.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.