

Imploding bubbles improve the growth of single-crystalline perovskite solar cell thin films

August 31 2016



Illustration of the growth process using bubbles. (a) bubbles are created by brief ultrasonic pulses. Credit: King Abdullah University of Science and Technology

Single thin-film crystals are required to utilize promising hybrid organic/inorganic perovskite materials to develop solar cells. Saudi Arabia's King Abdullah University of Science and Technology (KAUST)



researchers have now shown how imploding bubbles in a solution can grow single crystals of the preferred orientation for manufacturing thin films.

Hybrid organic/inorganic perovskite <u>materials</u> are some of the most promising solar cell materials, as they are easy to produce and show excellent solar light conversion efficiencies.

"Our monocrystalline films provide a platform to directly implement perovskite single crystals and to elucidate their promises and challenges for <u>solar cells</u>," said Osman Bakr, KAUST associate professor of material science and engineering who also led the research study.

Hybrid perovskite materials can easily be fabricated on a large scale from a solvent solution. However, this process typically produces polycrystalline perovskite films that have a smaller solar light conversion efficiency than monocrystalline materials because the boundary between crystalline grains leads to losses. In particular, growth of singlecrystalline perovskite solar cell films has not yet been achieved on top of other materials, which is a requirement for practical devices.

The researchers have now achieved the fabrication of single-crystalline perovskite <u>thin films</u> by applying ultrasonic pulses to the growth solution. The pulses induce tiny bubbles that implode after a short time, releasing energy into the surrounding solution. If a bubble is close to the substrate surface, the energy from the implosion creates tiny jets within the growth solution that are projected towards the substrate. Those jets induce the nucleation of perovskite crystals on the surface.





The bubbles implode, sending jets of growth liquid towards the substrate. Credit: King Abdullah University of Science and Technology

The films grown by this process are remarkably uniform and monocrystalline. Also, because of the directional impact of the liquid jets on the surface, the growth process is independent of the substrate properties and therefore leads to a favorable uniform orientation of the crystals. This alignment means they can support the transport of electrical charges across the device.

The thin films show very good conversion efficiencies. In test devices, a conversion efficiency of 6.5 percent was achieved, which is considerably higher than the 5.6 percent previously achieved from comparable polycrystalline samples.

There are further hurdles, however, Bakr noted. "The biggest challenge



of our method is the limited lateral dimensions that we can reach, which are only about two millimeters. The next step of our study is to improve the growth to reach centimeter-scale monocrystalline films or even larger sizes, which is essential for the large scale application of these monocrystalline <u>films</u> in industry," he said.



Monocrystalline thin films are grown. Credit: King Abdullah University of Science and Technology

More information: Solution-Grown Monocrystalline Hybrid Perovskite Films for Hole-Transporter-Free Solar Cells. *Advanced Materials* DOI: 10.1002/adma.201506292



Provided by King Abdullah University of Science and Technology

Citation: Imploding bubbles improve the growth of single-crystalline perovskite solar cell thin films (2016, August 31) retrieved 3 May 2024 from <u>https://phys.org/news/2016-08-imploding-growth-single-crystalline-perovskite-solar.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.