

New 3-D design for mobile microbatteries

October 11 2016

In the race towards miniaturization, a French-US team—mostly involving researchers from the CNRS, Université de Lille, Université de Nantes and Argonne National Laboratory (US) as part of the Research Network on Electrochemical Energy Storage (RS2E)¹—has succeeded in improving the energy density of a rechargeable battery without increasing its size (limited to a few square millimeters in mobile sensors). This feat was achieved by developing a 3-D structure made of microtubes, the first step towards producing a complete microbattery. The first experiments have demonstrated the excellent conductivity of the battery's solid electrolyte, whose highly encouraging performance is published in the journal *Advanced Energy Materials* on October 11, 2016.

In the era of connected devices, intelligent connected microsensors require miniature embedded energy sources with great energy density. For ultra-thin-or planar-microbatteries, increased [energy density](#) means using thicker layers of materials, which has obvious limitations. A second method—used by the authors of the publication—consists in machining a silicon wafer² and producing an original 3-D structure made of simple or double microtubes. 3-D batteries keep their 1mm² footprint area, but develop a specific area of 50 mm²—an enhancement factor of 50! These robust microtubes are large enough (of the order of the micron) to be coated with multiple layers of functional materials³.

The main technological challenge consisted precisely in depositing the different materials that make up the [rechargeable battery](#) in thin and regular layers on these complex 3-D structures. Using the [cutting edge](#)

[technology](#) of Atomic Layer Deposition (ALD), the materials perfectly took on the 3-D shape of the template without blocking the tube structures. In this way the researchers created an insulating thin film, a current collector, a negative electrode, and a solid electrolyte. The various analyses and characterizations (synchrotron X-ray nanotomography and transmission electron microscopy⁴) show that the successive layers are of excellent quality, showing conformality of nearly 100%. The interfaces are clean (no interdiffusion between the different chemical elements), with no pinholes, cracks, or fissures detected.

Lithium phosphate, the electrolyte of this future 3-D microbattery, is in solid form⁵. After depositing it using the same ALD technology, researchers showed that it has a high electrochemical stability window (4.2 V), high ionic conductivity, and low thickness (10 to 50 nm), which generates low surface resistance, all of which are very encouraging for the future performance of the 3-D battery.

The next step will consist in using ALD to develop thin films of positive electrode materials in order to create the first functional 3-D prototypes, which will certainly offer much greater performance than today's planar microbatteries.

More information: Atomic Layer Deposition of Functional Layers for on Chip 3D Li-Ion All Solid State Microbattery. *Adv. Energy Mater.*.. doi: 10.1002/aenm.201601402

Provided by CNRS

Citation: New 3-D design for mobile microbatteries (2016, October 11) retrieved 3 May 2024 from <https://phys.org/news/2016-10-d-mobile-microbatteries.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.