

New laser technology enables more sensitive gravitational-wave detectors

February 10 2017





The novel mode filter for laser beams in the LG33 mode, which was developed at the AEI. Top: mode filter in the laboratory. Bottom: schematic of the mode filter. Credit: Noack/Max Planck Institute for Gravitational Physics

One year ago, the first direct detection of gravitational waves was announced. Laser experts from the Max Planck Institute for Gravitational Physics (Albert Einstein Institute; AEI), from the Leibniz Universität Hannover, and from the Laser Zentrum Hannover e.V. (LZH) played leading roles in this discovery, because their super-precise laser technology at the heart of the LIGO instruments in the USA enabled the detection of weak gravitational-wave signals. Now, AEI researchers have presented two new technologies capable of further increasing the sensitivity of future gravitational-wave detectors. The Max Planck Society now strengthens the development of laser systems for third-generation gravitational-wave detectors. The AEI, in collaboration with the LZH, receives over the next five years 3.75 million Euro research funding for the development of novel lasers Zentrum Hannover receives over the next five years 3.75 million Euro research funding for the development of novel lasers and stabilization methods.

"We have made two important breakthroughs," says Apl. Prof. Benno Willke, leader of the laser development group at the AEI. "Our work is another step towards using a novel type of laser beam profile in interferometric gravitational-wave detectors. Furthermore, we have shown how to increase the power stability of the high-power lasers used in the detectors. These are important steps towards the future of gravitational-wave astronomy." The results were published in the renowned science journal *Optics Letters* and were highlighted by the editors.



More homogeneous laser beams

The beams of all laser systems currently used in gravitational-wave detectors have higher intensity at the centre than at the edges. This leads to an undesirable strong influence of mirror surface fluctuations on the measurement precision of gravitational-wave detectors. This so-called thermal noise can be reduced by a more homogeneous laser intensity distribution.

In 2013 a team with AEI involvement showed how more homogeneous high-power laser beams in the so-called LG_{33} mode can be created. Now, Andreas Noack has studied in his MSc thesis in Benno Willke's team how these laser beams can be fed into future gravitational-wave detectors.



Panorama shot of the 10 meter prototype at the Max Planck Institute for Gravitational Physics in Hannover. It is used for demonstrations and tests of technologies for the third generation of gravitational-wave detectors. Credit: Lück/Max Planck Institute for Gravitational Physics



The first step on the way into the detector is a device known as a premode cleaner, which optimizes the beam profile and reduces beam jitter. Willke's team showed that the new LG_{33} beam is incompatible with the pre-mode cleaners currently in use. The researchers also showed how to solve this problem. They developed a new pre-mode cleaner, which is compatible with the LG_{33} laser beams.

"The design of the next-generation gravitational wave detectors is not set," says Willke. "Therefore, we are testing different types of lasers to have as many options for new gravitational wave detectors as possible. We now have made a big step ahead with the promising LG_{33} beams."

Improving laser power stability for new gravitationalwave detectors

All interferometric gravitational-wave detectors like LIGO, Virgo, and GEO600 rely on laser systems that keep their high output power stable over years and that show very little short timescale power fluctuations. Benno Willke's research group plays a world-wide leading role in this research area. They constructed the laser systems for GEO600 and Advanced LIGO, without which the first direct detection of gravitational waves in September 2015 would not have been possible.





he photodetector system used for the power stabilization. Left: schematic of the beam path of the laser (red) onto the four measurement photo diodes via mirrors. Right: The device being integrated into the AEI 10 meter prototype. The four measurement photo diodes are on the right backside. The additional photodiodes for stabilization of the beam pointing are on the top, marked QPD1/2. Credit: Junker/Kwee/Max Planck Institute for Gravitational Physics

Now, Jonas Junker has further refined the existing power stabilization system in his MSc thesis in Willke's team. A part of the laser light is picked off and distributed on multiple photodetectors to precisely determine the total laser power. If it varies, the main laser power is corrected accordingly. In their experiment, the scientists extended the current system by adding, among other things, another photodetector to also control and correct the pointing of the laser beam.

The improved power stabilization scheme has been successfully applied to the 35 Watt laser system of the 10 meter prototype interferometer at the AEI. The prototype is used by researchers in Hannover for demonstrations and tests of technologies for the third generation of <u>detectors</u> and for research on quantum mechanical effects in these



instruments. The level of power stability reached is five times higher than that in comparable experiments of other groups. This value agrees very well with results from isolated table-top experiments.

"An experiment in the well isolated environment of an optical laboratory is completely different from a complex large-scale experiment like the 10 meter prototype. We have shown for the first time that it is possible to transfer the excellent stability level from a table-top experiment," says Willke. "We show that these photodiode arrays work as expected, meaning it should also be possible to achieve this high stability with the identical multi-photodetector arrays used in Advanced LIGO."

More information: Andreas Noack et al. Higher-order Laguerre–Gauss modes in (non-) planar four-mirror cavities for future gravitational wave detectors, *Optics Letters* (2017). <u>DOI:</u> <u>10.1364/OL.42.000751</u>

Provided by Max Planck Society

Citation: New laser technology enables more sensitive gravitational-wave detectors (2017, February 10) retrieved 3 May 2024 from <u>https://phys.org/news/2017-02-laser-technology-enables-sensitive-gravitational-wave.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.