

A simplified fabrication process for high efficiency solar cells

April 26 2017



Credit: CSEM / David Marchon

A team of EPFL and CSEM researchers in Neuchâtel presents in *Nature Energy* a new astonishing method of creating crystalline solar cells with electrical contacts at the rear, suppressing all shadowing at the front. Thanks to the new inexpensive approach, the fabrication process is strongly simplified with efficiencies in the laboratory already surpassing 23 percent.

In the quest for more efficient crystalline silicon [solar cells](#) with low manufacturing costs, one of the most promising [approach](#) is to bring all electrical contacts at the back of the device. This suppresses all shadowing at the front, increasing the current and the efficiency. This approach generally requires several delicate processing steps, because well-defined narrow negative and positive contact lines need to be created, which will then collect the electrons (negative charges) and holes (positive charges). This requires usually several steps of masking of photolithography to create the alternated positive (+) and negative (-) areas.

The team at the EPFL Photovoltaics laboratory and at the CSEM PV-center succeeded in establishing an innovative process in which the positive and negative contacts align automatically. This is made possible by depositing the first "negative" contact by plasma process through a mask. Subsequently, a second layer (positive) is deposited over the full surface. The growth of this layer is such that the negative contact, even covered with the positive contact, remains negative.

Using this simple [process](#), 25-cm² solar [cells](#) have already reached 23.2 percent efficiency, with the potential of reaching almost 26 percent. The researchers work with the Meyer Burger Company, a leading manufacturer of equipment for solar cell production lines, to work out industrial solutions for such solar cells, valorizing the so-called silicon heterojunctions technology that serve as the basis of this work.



Back of the solar cell, with positive and negative electrical contact. Front of the cell with no shadowing. Credit: Ecole Polytechnique Federale de Lausanne

More information: Andrea Tomasi et al. Simple processing of back-contacted silicon heterojunction solar cells using selective-area crystalline growth, *Nature Energy* (2017). DOI: [10.1038/nenergy.2017.62](https://doi.org/10.1038/nenergy.2017.62)

Provided by Ecole Polytechnique Federale de Lausanne

Citation: A simplified fabrication process for high efficiency solar cells (2017, April 26) retrieved 21 May 2024 from <https://phys.org/news/2017-04-fabrication-high-efficiency-solar-cells.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.