

## **Ceramic membranes separate tiny organic molecules with a molar mass of 200 Dalton**

May 30 2017



Ceramic membranes by the Fraunhofer Institute for Ceramic Technologies and Systems IKTS. Credit: Fraunhofer IKTS



Water is vital – therefore, waste water has to be cleaned as efficiently as possible. Ceramic membranes make this possible. Researchers from the Fraunhofer Institute for Ceramic Technologies and Systems IKTS in Hermsdorf, Germany were able to significantly reduce the separation limits of these membranes and to reliably filter off dissolved organic molecules with a molar mass of only 200 Dalton. Even industrial sewage water can thus be cleaned efficiently.

Anyone who has dragged himself along a sunny coastal path at the height of summer with too little water in his bag knows all too well: without water, we cannot make it too long. Water is one of the foundations of life. In industry, water is a must, as well: in many production processes, it serves as a solvent, detergent, to cool or to transfer heat. As more and more water is consumed, waste water has to be treated and reused. Ceramic membranes offer a good way to do this: since they are separated mechanically – similar to a coffee filter – they are particularly energy-efficient. However, this method previously came to an end when a molecular size of 450 Daltons was reached: smaller molecules could not be separated with <u>ceramic membranes</u>. According to experts, it was even considered impossible to go below this limit.

## Molecules as small as 200 Daltons can be separated

Dr. Ingolf Voigt, Dr.-Ing. Hannes Richter and Dipl.-Chem. Petra Puhlfuerss from the Fraunhofer IKTS have achieved the impossible. "With our ceramic membranes, we have achieved, for the first time, a molecular separation limit of 200 Daltons – and, thereby, a whole new quality," says Voigt, Deputy Institute Director of the IKTS and Site Manager in Hermsdorf.

But how did the researchers manage to do this? On the way to making the impossible possible, it was first necessary to overcome various obstacles. The first was in the production of the <u>membrane</u> itself: if such



small molecules were to be separated reliably, a membrane was needed that had pores smaller than the molecules which were to be separated. In addition, all of the pores had to be as similar in size as possible, since a single larger opening is sufficient to allow molecules to slip through. The challenge was therefore to produce pores which were as small as possible, with all of them having more or less the same size. "We achieved these results by refining sol-gel technology," says Richter, Head of Department at the IKTS. The second hurdle was to make such membrane layers defect-free over larger surfaces. The Fraunhofer researchers have succeeded in doing this, as well. "Whereas only a few square centimeters of surface are usually coated, we equipped a pilot system with a membrane area of 234 square meters, which means that our membrane is several magnitudes larger," explains Puhlfuerss, scientist at the IKTS.

## Transfer from the laboratory into practice

Commissioned by Shell, the pilot system was built by the company Andreas Junghans – Anlagenbau und Edelstahlbearbeitung GmbH & Co. KG in Frankenberg, Germany and is located in Alberta, Canada. There the system has been successfully purifying <u>waste water</u> since 2016, which is used for the extraction of oil from oil sand. The researchers are currently planning an initial production facility with a membrane area of more than 5,000 square meters.

The innovative ceramic membranes also offer advantages in industrial production processes: they can be used to purify partial currents directly in the process as well as to guide the cleaned water in the cycle, which saves water and energy.

For the development of the ceramic nanofiltration membrane, Dr. Ingolf Voigt, Dr.-Ing. Hannes Richter and Dipl.-Chem. Petra Puhlfuerss received this year's Joseph von Fraunhofer Prize. The jury justifies the



award by mentioning, among other things, "the first-ever realization for filtration applications within this material class."

Provided by Fraunhofer-Gesellschaft

Citation: Ceramic membranes separate tiny organic molecules with a molar mass of 200 Dalton (2017, May 30) retrieved 24 April 2024 from <u>https://phys.org/news/2017-05-ceramic-membranes-dissolve-tiny-molecules.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.