


Nanoparticles could spur better LEDs, invisibility cloaks

July 19 2017



A microscopy photo showing an array of precisely placed metallic nanoparticles on the surface of a gallium arsenide semiconductor. Credit: Courtesy of Rachel S. Goldman, Michigan Engineering


In an advance that could boost the efficiency of LED lighting by 50 percent and even pave the way for invisibility cloaking devices, a team of University of Michigan researchers has developed a new technique that peppers metallic nanoparticles into semiconductors.

It's the first technique that can inexpensively grow metal nanoparticles both on and below the surface of semiconductors. The process adds virtually no cost during manufacturing and its improved efficiency could allow manufacturers to use fewer semiconductors in finished products, making them less expensive.

The [metal nanoparticles](#) can increase the efficiency of LEDs in several ways. They can act as tiny antennas that alter and redirect the electricity running through the semiconductor, turning more of it into light. They can also help reflect light out of the device, preventing it from being trapped inside and wasted.

The process can be used with the gallium nitride that's used in LED lighting and can also boost efficiency in other semiconductor products, including solar cells. It's detailed in a study published in the *Journal of Applied Physics*.

"This is a seamless addition to the manufacturing process, and that's what makes it so exciting," said Rachel Goldman, U-M professor of materials science and engineering, and physics. "The ability to make 3-D structures with these nanoparticles throughout is going to open a lot of possibilities."



Gallium arsenide nanoparticles forming on the surface of a semiconductor. Courtesy of Rachel S. Goldman, University of Michigan professor of materials science and engineering

The key innovation

The idea of adding nanoparticles to increase LED efficiency is not new. But previous efforts to incorporate them have been impractical for large-scale manufacturing. They focused on pricey metals like silver, gold and platinum. In addition, the size and spacing of the particles must be very precise; this required additional and expensive manufacturing steps. Furthermore, there was no cost-effective way to incorporate particles below the surface.

Goldman's team discovered a simpler way that integrates easily with the [molecular beam epitaxy](#) process used to make semiconductors.

Molecular beam epitaxy sprays multiple layers of metallic elements onto a wafer. This creates exactly the right conductive properties for a given purpose.

The U-M researchers applied an [ion beam](#) between these layers—a step that pushes metal out of the semiconductor wafer and onto the surface. The metal forms nanoscale particles that serve the same purpose as the pricey gold and platinum flecks in earlier research. Their size and placement can be precisely controlled by varying the angle and intensity of the ion beam. And applying the ion beam over and over between each layer creates a semiconductor with the nanoparticles interspersed throughout.

"If you carefully tailor the size and spacing of nanoparticles and how deeply they're embedded, you can find a sweet spot that enhances light emissions," said Myungkoo Kang, a former graduate student in Goldman's lab and first author on the study. "This process gives us a much simpler and less expensive way to do that."

Researchers have known for years that metallic particles can collect on the surface of semiconductors during manufacturing. But they were always considered a nuisance, something that happened when the mix of elements was incorrect or the timing was off.



The main growth chamber of the molecular epitaxy beam apparatus used to make the nanoparticle-infused gallium nitride semiconductors. The semiconductors could boost LED efficiency by up to 50 percent, and even lead to invisibility cloaking devices. Credit: Photo by Joseph Xu, Michigan Engineering Communications & Marketing

"From the very early days of [semiconductor](#) manufacturing, the goal was always to spray a smooth layer of elements onto the surface. If the elements formed particles instead, it was considered a mistake," Goldman said. "But we realized that those 'mistakes' are very similar to the particles that manufacturers have been trying so hard to incorporate into LEDs. So we figured out a way to make lemonade out of lemons."

Toward invisibility cloaks

Because the technique allows precise control over the nanoparticle distribution, the researchers say it may one day be useful for cloaks that render objects partially invisible by inducing a phenomenon known as "reverse refraction."

Reverse refraction bends light waves backwards in a way that doesn't occur in nature, potentially directing them around an object or away from the eye. The researchers believe that by carefully sizing and spacing an array of [nanoparticles](#), they may be able to induce and control reverse refraction in specific wavelengths of light.

"For [invisibility cloaking](#), we need to both transmit and manipulate light in very precise ways, and that's very difficult today," Goldman said. "We believe that this process could give us the level of control we need to make it work."

The team is now working to adapt the ion beam process to the specific materials used in LEDs—they estimate that the higher-efficiency lighting devices could be ready for market within the next five years, with invisibility cloaking and other applications coming further in the future.

The study is titled "Formation of embedded plasmonic Ga nanoparticle arrays and their influence on GaAs photoluminescence."

More information: Formation of embedded plasmonic Ga nanoparticle arrays and their influence on GaAs photoluminescence, *Journal of Applied Physics*, 2017.

Provided by University of Michigan

Citation: Nanoparticles could spur better LEDs, invisibility cloaks (2017, July 19) retrieved 23 April 2024 from <https://phys.org/news/2017-07-nanoparticles-spur-invisibility-cloaks.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.