

Aligning the primary mirror segments of NASA's James Webb Space Telescope with light

September 20 2017



Artist rending showing light reflecting off of the primary and secondary mirrors of NASA's James Webb Space Telescope, after it has deployed in space. Credit: NASA/Mike McClare

Engineers at NASA's Johnson Space Center in Houston used light waves to align the James Webb Space Telescope's mirror segments to each other, so they act like a single, monolithic mirror in the cryogenic cold



of the center's iconic Chamber A.

Part of the Webb <u>telescope</u>'s ongoing cryogenic testing in Chamber A at Johnson includes aligning, or "phasing," the telescope's 18 hexagonally shaped <u>primary mirror</u> segments so they function as a single 6.5-meter mirror. All of these segments must have the correct position and correct curvature; otherwise, the telescope will not be able to accurately focus on its celestial targets.

Aligning the mirrors

To measure the shape of the Webb telescope's primary mirror, engineers use a test device called an interferometer, which shines a laser down onto the mirror. Because the mirror is segmented, it requires a specially designed interferometer, known as a multi-wavelength interferometer, which allows the engineers to use two light waves at once, explained Lee Feinberg, optical telescope element manager for the Webb telescope at NASA's Goddard Space Flight Center in Greenbelt, Maryland.

The interferometer splits the laser light into two separate waves. One of these waves goes through a lens and reflects off the primary mirror; the other wave acts as a reference. The reflected wave interferes with (meets) the reference wave, and engineers analyze the combined wave that results from that interference. "By analyzing the interference signal, engineers determine the mirror shape and the alignment of the mirrors," explained Feinberg.

When the engineers need to adjust the positions and shapes of the mirror segments to achieve precise alignment, they use the seven actuators (tiny mechanical motors) attached to the back of each one of the <u>mirror</u> <u>segments</u>. For each segment, six of these actuators are placed into groups of two, at three equally spaced points along the outside of the mirror (to adjust the segment's position), and one is attached to six struts that are



connected to each of the hexagonal mirror segment's corners (to adjust the segment's shape).

The actuators on each mirror segment are capable of extremely minute movements, which allow engineers to align the entire primary mirror by finely adjusting each mirror segment. "They can move in steps that are a fraction of a wavelength of light, or about 1/10,000th the diameter of a human hair," explained Feinberg.

These actuators can also be used to precisely reshape each mirror segment to ensure they all match up once aligned. The ability to change the mirror alignment and shape is critical because the mirror must be unfolded from its unaligned stowed position when the telescope deploys. This test verifies the actuators have enough range of movement once they are in space, at their operational temperature of about 40 K (or about minus 388 degrees Fahrenheit / minus 233 degrees Celsius), to put the telescope's primary mirror into its correct shape so it can accurately survey the universe.

Testing the aligned mirrors

With the mirrors aligned, engineers test Webb's optics using a piece of support equipment called the ASPA, a nested acronym that means "AOS Source Plate Assembly." The ASPA is a piece of test hardware that sits atop Webb's Aft Optics Subsystem (AOS) and sends test laser light into and out of the telescope, thus acting like a source of artificial starlight. The AOS contains the telescope's tertiary and fine-steering mirrors.





Strut

When the center actuator

moves up or down, it pulls or pushes on the six struts, which in turn correctly curves the mirror.

JWST Primary Mirror Segment

(1/5th scale model)

Actuator

The actuators are tiny mechanical motors that move the mirrors into proper alignment and curvature with each other.

Each mirror has seven actuators—six at the hexapod ends and one in the center.

Beryllium Substrate

Beryllium was chosen for the mirror's "skeleton" because it's strong and light, and will hold its shape in the extreme cold of space.

The substrate was machined in a honeycomb pattern to remove excess material and thus decrease its weight, yet maintain its strength.

Hexapod

When the actuators at the hexapod ends pull or push on the hexapod, it pulls or pushes the mirror into correct alignment with the other mirrors.

Electronics Box

Every mirror segment has one electronics box. This box sends signals to the actuators to steer, position, and control the mirrors.

The electronics boxes are located within the backplane—the structure that holds all the mirrors.

D1949_JWST Mini-Mittor

Each one of the primary mirror segments of NASA's James Webb Space



Telescope has an assembly with seven actuators called a hexapod. Credit: Ball Aerospace

During one part of the optical test, called the "half-pass" test, the ASPA feeds laser light straight into the AOS, where it is directed by the tertiary and fine-steering mirrors to Webb's four science instruments, which sit in a compartment directly behind the primary mirror. This test lets engineers make measurements of the optics inside the AOS to verify that Webb's tertiary mirror, which is immovable, is correctly aligned to the instruments.

In another part of the test, called the "pass-and-a-half" test, light travels in a reverse path through the telescope optics. The light is again fed into the system from the ASPA, but upwards this time, to the secondary mirror. The secondary mirror reflects the light down to the primary mirror, which sends it back up to the top of Chamber A. Mirrors at the top of the chamber send the <u>light</u> back down to the telescope again, where it follows its normal course through the telescope to the instruments, but this time bypassing the ASPA test equipment.

"This verifies not only the alignment of the primary mirror itself but also the alignment of the whole telescope—the primary mirror, secondary <u>mirror</u>, and the tertiary and fine-steering mirrors inside the AOS," said Paul Geithner, the deputy project manager - technical for Webb telescope at Goddard. "Taken together, the half-pass and pass-and-a-half tests demonstrate that everything is aligned to everything else."

Because the ASPA is ground <u>test</u> hardware, it will be removed from the telescope once the cryogenic testing at Johnson is complete.

The cryogenic vacuum environment of Chamber A simulates the frigid



space environment where Webb will operate, and where it will collect data of never-before-observed portions of the universe. Verifying the entire telescope, including its optics and instruments, works correctly in this cold environment ensures the telescope will work correctly in space. The telescope and its instruments are designed to operate cold, so they must be cold to be aligned and to properly function.

The James Webb Space Telescope is the scientific complement to NASA's Hubble Space Telescope. It will be the most powerful space telescope ever built. Webb is an international project led by NASA with its partners, ESA (European Space Agency) and the CSA (Canadian Space Agency).

Provided by NASA's Goddard Space Flight Center

Citation: Aligning the primary mirror segments of NASA's James Webb Space Telescope with light (2017, September 20) retrieved 1 May 2024 from <u>https://phys.org/news/2017-09-aligning-primary-mirror-segments-nasa.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.