

3-D printing materials for wound care and decorative elements

September 18 2017

Cellulose nanofibrils have properties that can improve the characteristics of bio-based 3-D-printing pastes. VTT Technical Research Centre of Finland is developing a 3-D wound care product for monitoring wound condition in hospital care. However, the first commercial nanocellulose applications will be seen in indoor decoration elements, textiles and the production of mock-ups.

3-D printing has proven to be an efficient manufacturing method for complex, customised and light structures. In addition to thermoplastics, 3-D printing materials include metals, ceramics and foodstuffs. The range of biomaterials in 3-D paste printing is still fairly limited, since pastes pose unique challenges: their structure must not collapse during printing and the objects manufactured must remain sufficiently strong, rigid or flexible after drying. In 3-D biomaterial filaments, however, commercial products already exist.

Cellulose nanofibrils offer an opportunity for developing durable, bio-based commercial 3-D-printing materials. They can offer an alternative to the currently used chemicals, such as resins, synthetic thickeners, strengtheners and plastics, the use of which might generate harmful emissions and even allergising compounds.

3-D technology in wound care

Nanocellulose is an attractive option for medical applications, for

example as a carrier of drug molecules. VTT is currently developing a solution where a protein attached to a 3-D-printed adhesive bandage can help to promote the growth of skin cells around a wound. The purpose is to have the healed wound area remain flexible instead of it developing stiff scar tissue. The development is done in collaboration with the University of Tampere and funded by The Academy of Finland under the BioDisp3D programme. The same materials development process can also be used in the cosmetics industry or in the manufacture of artificial bone, for example.

"By using nanocellulose, we have succeeded in creating 3-D structures that absorb liquids three times more efficiently than the compared alginate fibre dressings commonly used in wound care," says Senior Scientist Panu Lahtinen from VTT.

VTT's wound care prototype combines nanocellulose, a protein used in wound care, and printed electronics measuring wound healing into a single product. The measurement electrodes were printed with silver ink onto a film made of polyurethane-nanocellulose, with the electrodes providing connection points for the wireless FlexNode reader developed at VTT. The electrodes are protected by another laminated layer of the film. On top of this lamination lies a 3-D-printed wound care gel containing nanocellulose, alginate and glycerol as the active ingredients. The FlexNode reader transmits temperature or bioimpedance data from the wound wirelessly to a computer used by the health care team. The reader can be connected to the wound and attached to the patient with gauze.

Nanocellulose has not yet been approved for medical use, which means that it will take several years before this application is used in hospitals.

Decorative elements

VTT is also developing bio-based printing materials for modifying textiles, mock-ups, indoor decoration elements and therapy applications in [wound care](#) under the DWoc and NoMA projects funded by Tekes - the Finnish Funding Agency for Innovation. By selecting appropriate combinations of materials, it is possible to print both flexible and rigid structures, depending on the need. Product properties can also be customised by other means.

Nanocellulose increases the opportunities for creating new surface patterns in decorative elements. The development still requires light and moisture tests in various applications. Printing materials can also be used for 3-D-printing customised moulds.

Cellulose nanofibrils

Manufactured for example from cellulose or the side streams of agricultural or food production, Cellulose nanofibrils (CNF) are suitable for 3-D printing pastes thanks to their mechanical strength, effects on viscosity and biodegradability. In particular, CNFs can be used for improving the rigidity of 3-D-structures. The way the fibrils are cross-linked affects the properties of the structure: moisture tolerance, rigidity and flexibility.

Due to the excellent water absorption capacity of CNFs, printing pastes can be made viscous enough for the 3-D printing process. A 3-D printing paste can contain up to 50 percent of water without the paste running during [printing](#).

VTT has used CNFs to develop flexible, rigid and porous structures. Manufacturing a flexible structure out of bio-based materials is challenging, since the object tends to harden and become more rigid as it dries.

More information: Jenni Leppiniemi et al. 3D-Printable Bioactivated Nanocellulose–Alginate Hydrogels, *ACS Applied Materials & Interfaces* (2017). [DOI: 10.1021/acsami.7b02756](https://doi.org/10.1021/acsami.7b02756)

Presentation: Lahtinen&al., Multicomponent printing pastes for 3D printing bio-based hydrogels, Biofor 2017, Montreal 15 February 2017.

Presentation: Tenhunen et al., 3D-printing of cellulosic materials – properties and suitability on cellulosic fabrics, 253rd ACS national meeting, San Francisco 2-6 April 2017.

Provided by VTT Technical Research Centre of Finland

Citation: 3-D printing materials for wound care and decorative elements (2017, September 18) retrieved 10 April 2024 from <https://phys.org/news/2017-09-d-materials-wound-elements.html>

<p>This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.</p>
--