

Researchers create predictable patterns from unpredictable carbon nanotubes

February 14 2018, by Denis Paiste



A recolored optical image obtained by MIT researchers shows a heart-shaped carbon nanotube cell. A version of the image is featured on the cover of the Feb. 14 print edition of Physical Chemistry Chemical Physics. Credit: Ashley Kaiser and Itai Stein/MIT

Integrating nanoscale fibers such as carbon nanotubes (CNTs) into



commercial applications, from coatings for aircraft wings to heat sinks for mobile computing, requires them to be produced in large scale and at low cost. Chemical vapor deposition (CVD) is a promising approach to manufacture CNTs in the needed scales, but it produces CNTs that are too sparse and compliant for most applications.

Applying and evaporating a few drops of a liquid such as acetone to the CNTs is an easy, cost-effective method to more tightly pack them together and increase their stiffness, but until now, there was no way to forecast the geometry of these CNT cells.

MIT researchers have now developed a systematic method to predict the two-dimensional patterns CNT arrays form after they are packed together, or densified, by evaporating drops of either acetone or ethanol. CNT cell size and wall stiffness grow proportionally with cell height, they report in the Feb. 14 issue of *Physical Chemistry Chemical Physics*.

One way to think of this CNT behavior is to imagine how entangled fibers such as wet hair or spaghetti collectively reinforce each other. The larger this entangled region is, the higher its resistance to bending will be. Similarly, longer CNTs can better reinforce one another in a cell wall. The researchers also find that CNT binding strength to the base on which they are produced, in this case, silicon, makes an important contribution to predicting the cellular patterns that these CNTs will form.

"These findings are directly applicable to industry because when you use CVD, you get nanotubes that have curvature, randomness, and are wavy, and there is a great need for a method that can easily mitigate these defects without breaking the bank," says Itai Stein SM '13, Ph.D. '16, who is a postdoc in the Department of Aeronautics and Astronautics. Coauthors include materials science and engineering graduate student Ashley Kaiser, mechanical engineering postdoc Kehang Cui, and senior



author Brian Wardle, professor of aeronautics and astronautics.



Aligned carbon nanotubes (CNTs) grown by chemical vapor deposition are typically wavy, as seen in side view at center of illustration, rather than straight, as illustrated in a single nanotube at right. They also settle into somewhat random patterns, as shown in box at upper left. Waviness reduces the stiffness of CNT arrays by up to 100,000 times, but their stiffness can be increased by densifying, or compressing, the nanotube clusters from two different directions. Credit: Itai Stein/MIT

"From our previous work on aligned carbon nanotubes and their composites, we learned that more tightly packing the CNTs is a highly effective way to engineer their properties," says Wardle. "The



challenging part is to develop a facile way of doing this at scales that are relevant to commercial aircraft (hundreds of meters), and the predictive capabilities that we developed here are a large step in that direction."

Detailed measurements

Carbon nanotubes are highly desirable because of their thermal, electrical, and mechanical properties, which are directionally dependent. Earlier work in Wardle's lab demonstrated that waviness reduces the stiffness of CNT arrays by as little as 100 times, and up to 100,000 times. The technical term for this stiffness, or ability to bend without breaking, is elastic modulus. Carbon nanotubes are from 1,000 to 10,000 times longer than they are thick, so they deform principally along their length.

For an earlier paper published in the journal *Applied Physics Letters*, Stein and colleagues used nanoindentation techniques to measure stiffness of aligned <u>carbon nanotube</u> arrays and found their stiffness to be 1/1,000 to 1/10,000 times less than the theoretical stiffness of individual carbon nanotubes. Stein, Wardle, and former visiting MIT graduate student Hülya Cebeci also developed a theoretical model explaining changes at different packing densities of the nanofibers.

The new work shows that CNTs compacted by the capillary forces from first wetting them with acetone or ethanol and then evaporating the liquid also produces CNTs that are hundreds to thousands of times less stiff than expected by theoretical values. This capillary effect, known as elastocapillarity, is similar to a how a sponge often dries into a more compact shape after being wetted and then dried.





A scanning electron microscope image shows that heat-treated aligned carbon nanotubes self-assemble into cells with clearly defined cell walls when they are densified by applying and evaporating a few drops of liquid acetone or ethanol. MIT researchers have developed a systematic method to predict the geometry of the two-dimensional cellular patterns that these nanotubes will form. Bright lines represent top edges of cell walls, while darker portions represent nanotubes closer to the silicon substrate base, which is seen in the flat spaces between cell walls. Credit: Ashley Kaiser/MIT

"Our findings all point to the fact that the CNT wall modulus is much lower than the normally assumed value for perfect CNTs because the underlying CNTs are not straight," says Stein. "Our calculations show that the CNT wall is at least two orders of magnitude less stiff than we expect for straight CNTs, so we can conclude that the CNTs must be



wavy."

Heat adds strength

The researchers used a heating technique to increase the adhesion of their original, undensified CNT arrays to their silicon wafer substrate. CNTs densified after heat treatment were about four times harder to separate from the silicon base than untreated CNTs. Kaiser and Stein, who share first authorship of the paper, are currently developing an analytical model to describe this phenomenon and tune the adhesion force, which would further enable prediction and control of such structures.

"Many applications of vertically aligned carbon nanotubes [VACNTs], such as electrical interconnects, require much denser arrays of nanotubes than what is typically obtained for as-grown VACNTs synthesized by chemical vapor deposition," says Mostafa Bedewy, assistant professor at the University of Pittsburgh, who was not involved in this work. "Hence, methods for postgrowth densification, such as those based on leveraging elastocapillarity have previously been shown to create interesting densified CNT structures. However, there is still a need for a better quantitative understanding of the factors that govern cell formation in densified large-area arrays of VACNTs. The new study by the authors contributes to addressing this need by providing experimental results, coupled with modeling insights, correlating parameters such as VACNT height and VACNT-substrate adhesion to the resulting cellular morphology after densification.

"There are still remaining questions about how the spatial variation of CNT density, tortuosity [twist], and diameter distribution across the VACNT height affects the capillary densification process, especially since vertical gradients of these features can be different when comparing two VACNT arrays having different heights," says Bedewy.



"Further work incorporating spatial mapping of internal VACNT morphology would be illuminating, although it will be challenging as it requires combining a suite of characterization techniques."



(Detail of previous image.) MIT researchers report that CNT cell size and wall stiffness grow proportionally with cell height. Credit: Ashley Kaiser/MIT

Picturesque patterns

Kaiser, who was a 2016 MIT Summer Scholar, analyzed the densified CNT arrays with scanning electron microscopy (SEM) in the MIT Materials Research Laboratory's NSF-MRSEC-supported Shared Experimental Facilities. While gently applying liquid to the CNT arrays



in this study caused them to densify into predictable cells, vigorously immersing the CNTs in liquid imparts much stronger forces to them, forming randomly shaped CNT networks. "When we first started exploring densification methods, I found that this forceful technique densified our CNT arrays into highly unpredictable and interesting patterns," says Kaiser. "As seen optically and via SEM, these patterns often resembled animals, faces, and even a heart—it was a bit like searching for shapes in the clouds." A colorized version of her optical image showing a CNT heart is featured on the cover of the Feb. 14 print edition of *Physical Chemistry Chemical Physics*.

"I think there is an underlying beauty in this nanofiber self-assembly and densification process, in addition to its practical applications," Kaiser adds. "The CNTs densify so easily and quickly into patterns after simply being wet by a liquid. Being able to accurately quantify this behavior is exciting, as it may enable the design and manufacture of scalable nanomaterials."

More information: Ashley L. Kaiser et al. Process-morphology scaling relations quantify self-organization in capillary densified nanofiber arrays, *Physical Chemistry Chemical Physics* (2018). DOI: 10.1039/c7cp06869g

Itai Y. Stein et al. Aligned carbon nanotube array stiffness from stochastic three-dimensional morphology, *Nanoscale* (2015). DOI: 10.1039/C5NR06436H

Hülya Cebeci et al. Effect of nanofiber proximity on the mechanical behavior of high volume fraction aligned carbon nanotube arrays, *Applied Physics Letters* (2014). DOI: 10.1063/1.4862273

This story is republished courtesy of MIT News



(<u>web.mit.edu/newsoffice/</u>), a popular site that covers news about MIT research, innovation and teaching.

Provided by Massachusetts Institute of Technology

Citation: Researchers create predictable patterns from unpredictable carbon nanotubes (2018, February 14) retrieved 3 May 2024 from <u>https://phys.org/news/2018-02-patterns-unpredictable-carbon-nanotubes.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.