

## **Power-to-gas facility with high efficiency**

## March 2 2018



Demonstrator facility of the HELMETH project combines methanation (left) and electrolysis (right) with an efficiency of 76 percent. Credit: sunfire GmbH

The natural gas network may serve as a buffer for weather-dependent electricity from the wind and sun. This requires economically efficient processes to use electricity for the production of chemical energy carriers. The EU project HELMETH coordinated by KIT has now made



an important step, demonstrating that high-temperature electrolysis and methanation can be combined in a power-to-gas process with an efficiency of more than 75 percent.

"For the first time, we used the synergies between electrolysis and methanation and reached an efficiency that exceeds that of standard technologies by about 20 percent," says Dimosthenis Trimis of KIT, coordinator of the HELMETH EU project. "Thanks to the large scope of disciplines covered by our consortium, we managed to reach an important milestone for mastering the energy transition."

A conventional industrial power-to-gas facility converts about 54 percent of the electric energy of renewable power into chemical energy of methane fuel. The prototype of the HELMETH EU project that fits into two conventional sea freight containers of about 6 m length each reached an efficiency of 76 percent in the final measurements. This gives hope for reaching an efficiency of 80 percent on the industrial scale. In parallel, economic efficiency and the climate balance of the new technology were studied. "These high efficiencies make the power-togas technology a very promising one," Trimis says. Efficiencies of more than 80 percent appear to be possible, provided that the limiting process steps identified in HELMETH will be addressed in future research.

A big potential leveraged in HELMETH was the optimal use of process heat from methanation to cover heat consumption of electrolysis. Hightemperature electrolysis at about 800°C and high pressure has thermodynamic advantages that cause the efficiency to increase. During electrolysis, the power is used first to decompose water into oxygen and the energy carrier hydrogen. Then, hydrogen reacts with carbon dioxide or carbon monoxide to methane, the main constituent of <u>natural gas</u>, with heat being released. The advantage of methane over hydrogen consists in the fact that it can be fed into the existing natural gas intrastructure without any limitations or any further processing. Feeding



of pure hydrogen into the network may possibly require bigger adaptation efforts in transportation and use, as the energy density and chemical properties differ considerably. The natural gas substitute produced within the HELMETH project always contained hydrogen concentrations below 2 vol. percent. Hence, it could be fed into the entire German natural gas network without any restrictions.

## Provided by Karlsruhe Institute of Technology

Citation: Power-to-gas facility with high efficiency (2018, March 2) retrieved 2 May 2024 from <u>https://phys.org/news/2018-03-power-to-gas-facility-high-efficiency.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.