


Image: CubeSat micro-pulsed plasma thruster

June 13 2018



Credit: ESA/Mars Space

This micro-pulsed plasma thruster has been designed for propulsion of

miniature CubeSats; its first firing is seen here. The thruster works by pulsing a lightning-like electric arc between two electrodes. This vaporizes the thruster propellant into charged plasma, which is then accelerated in the electromagnetic field set up between the electrodes.

Developed for ESA by Mars Space Ltd and Clyde Space of the UK with Southampton University, this 2 Watt, 42 Newton-second impulse plasma thruster has been qualified for [space](#), with more than a million firing pulses demonstrated during testing.

It has been designed for a range of uses, including drag compensation in low orbits, orbit maintenance, formation flying and small [orbit](#) transfers. The thruster could also serve as a CubeSat deorbiting device, gradually reducing orbital altitude until atmospheric re-entry is achieved.

About the size of a DVD reader, the [thruster](#) weighs just 280 grams including its propellant load and drive electronics.

Provided by European Space Agency

Citation: Image: CubeSat micro-pulsed plasma thruster (2018, June 13) retrieved 19 April 2024 from <https://phys.org/news/2018-06-image-cubesat-micro-pulsed-plasma-thruster.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.