

# A protective shield for sensitive enzymes in biofuel cells

September 17 2018

---



The biofuel cell tests were carried out in this electrochemical cell. Credit: Ruhr-Universitaet-Bochum

An international team of researchers has developed a new mechanism to protect enzymes from oxygen as biocatalysts in fuel cells. The enzymes,

known as hydrogenases, are just as efficient as precious metal catalysts, but unstable when they come into contact with oxygen. They are therefore not yet suitable for technological applications. The new protective mechanism is based on oxygen-consuming enzymes that draw their energy from sugar. The researchers showed that they were able to use this protective mechanism to produce a functional biofuel cell that works with hydrogen and glucose as fuel.

The team led by Dr. Adrian Ruff and Professor Wolfgang Schuhmann from the Center for Electrochemical Sciences at Ruhr-Universität Bochum describes the results in the journal *Nature Communications* from 10 September 2018 together with colleagues from the Max Planck Institute for Chemical Energy Conversion in Mülheim an der Ruhr and the University of Lisbon.

The team from the Bochum Center for Electrochemical Sciences had already shown in earlier studies that hydrogenases can be protected from [oxygen](#) by embedding them in a polymer. "However, this mechanism consumed electrons, which reduced the performance of the fuel cell," says Adrian Ruff. "In addition, part of the catalyst was used to protect the [enzyme](#)." The scientists therefore looked for ways to decouple the catalytically active system from the [protective mechanism](#).

## Enzymes trap oxygen

With the aid of two enzymes, they built an oxygen removal system around the current-producing electrode. First, the researchers coated the electrode with the hydrogenases, which were embedded in a polymer matrix to fix them in place. They then placed another polymer matrix on top of the hydrogenase, which completely enclosed the underlying catalyst layer. It contained two enzymes that use sugar to convert oxygen into water.

Hydrogen is oxidised in the hydrogenase-containing layer at the bottom. The electrode absorbs the electrons released in the process. The top layer removes harmful oxygen.

## Functional fuel cell built

In further experiments, the group combined the bioanodes described above with biocathodes, which are also based on the conversion of glucose. In this way, the team produced a functional biofuel cell. "The cheap and abundant biomass glucose is not only the fuel for the protective system, but also drives the biocathode and thus generates a current flow in the cell," summarises Wolfgang Schuhmann, head of the Center for Electrochemical Sciences and member of the cluster of excellence Ruhr Explores Solvation. The cell had an open-circuit voltage of 1.15 volts – the highest value ever achieved for a cell containing a polymer-based bioanode.

"We assume that the principle behind this protective shield [mechanism](#) can be transferred to any sensitive catalyst if the appropriate enzyme is selected that can catalyse the corresponding interception reaction," says Wolfgang Schuhmann.

**More information:** Adrian Ruff et al. A fully protected hydrogenase/polymer-based bioanode for high-performance hydrogen/glucose biofuel cells, *Nature Communications* (2018). [DOI: 10.1038/s41467-018-06106-3](https://doi.org/10.1038/s41467-018-06106-3)

Provided by Ruhr-Universitaet-Bochum

Citation: A protective shield for sensitive enzymes in biofuel cells (2018, September 17)  
retrieved 30 April 2024 from

<https://phys.org/news/2018-09-shield-sensitive-enzymes-biofuel-cells.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.