

## X-ray analysis of carbon nanostructures helps material design

March 14 2019



Schematic view of carbon structures with pores. Credit: HZB

Nanostructures made of carbon are extremely versatile. They can absorb ions in batteries and supercapacitors, store gases and desalinate water. How well they cope with the task at hand depends largely on the structural features of the nanopores. A new study from the HZB has now shown that structural changes that occur due to morphology transition with increasing temperature of the synthesis can also be measured directly, using small-angle X-ray scattering. The results have now been published in the journal *Carbon*.

Optimized nanoporous carbons can serve as electrodes for fast electron and ion transport or improve the performance of energy storage and



conversion devices. Thus the tunability of the size, shape, and distribution of pores is highly required. The team at the HZB Institute for Soft Matter and Functional Materials collaborated with a group at the University of Tartu, Estonia, to inquire the nanoarchitecture, inner <u>surface</u>, size, form and distribution of <u>nanopores</u> in dependence of the synthesis conditions.

Colleagues in Estonia produced a series of nanoporous carbons by reacting a powder of molybdenum carbide ( $Mo_2C$ ) with gaseous chlorine at 600, 700, 800, 900, and 1000 degrees Celsius. Depending on the synthesis conditions chosen, the nanoporous carbon exhibit different properties such as surface area, porosity, electronic and ionic conductivity, hydrophilicity and electrocatalytic activity.

Surface structures were analysed by transmission electron microscopy at the HZB. The interior surface area of nanocarbon materials is usually investigated by adsorption of gas. However, this method is not only comparatively inaccurate, it also contains no information about the shape and size of the pores. For deeper insights, Dr. Eneli Härk and her colleagues at HZB worked with small-angle X-ray scattering, a technique permitting to obtain information on various structural features on the nanometer scale including the mean pore size.

Small-angle X-ray scattering not only provides information on the precise inner <u>surface area</u> and the average <u>pore</u> size, but also on their angularity, i.e., sharp edges of formed pores, which play a major role for the functionalization of the materials. "The SAXS analysis summarizes over an enormous amount of micropores omitting misleading assumptions thereby directly relating the nanostructural architecture of the material to macroscopic technical parameters under investigation in engineering," Härk explains.

The main aim was to understand structural formation, and



electrochemical characteristics of <u>carbon</u> as a function of the synthesis temperature. "For optimal function, not only the high <u>inner surface</u> area is crucial, but the pores should have exactly the right shape, size and distribution," says Härk.

**More information:** Eneli Härk et al, Carbide derived carbons investigated by small angle X-ray scattering: Inner surface and porosity vs. graphitization, *Carbon* (2019). <u>DOI: 10.1016/j.carbon.2019.01.076</u>

## Provided by Helmholtz Association of German Research Centres

Citation: X-ray analysis of carbon nanostructures helps material design (2019, March 14) retrieved 3 May 2024 from https://phys.org/news/2019-03-x-ray-analysis-carbon-nanostructures-material.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.