

Flexible circuits for 3-D printing

April 29 2019



Example of a flexible and transparent electronic component: a flexible capacitor.

Credit: University of Hamburg, Tomke Glier

A research collaborative between the University of Hamburg and DESY has developed a process suitable for 3-D printing that can be used to produce transparent and mechanically flexible electronic circuits. The electronics consists of a mesh of silver nanowires that can be printed in suspension and embedded in various flexible and transparent plastics (polymers). This technology can enable new applications such as printable light-emitting diodes, solar cells or tools with integrated circuits, as Tomke Glier from the University of Hamburg and her colleagues report in the journal *Scientific Reports*. The researchers are demonstrating the potential of their process with a flexible capacitor, among other things.

"The aim of this study was to functionalize 3-D-printable polymers for different applications," reports Michael Rübhausen from the Center for Free-Electron Laser Science (CFEL), a cooperation between DESY, the University of Hamburg and the Max Planck Society. "With our novel approach, we want to integrate electronics into existing structural units and improve components in terms of space and weight." The physics professor from the University of Hamburg led the project together with DESY researcher Stephan Roth, who is also professor at the Royal Institute of Technology in Stockholm. Using the bright X-ray light from DESY's research light source PETRA III and other measuring methods, the team has precisely analyzed the properties of the nanowires in the [polymer](#).

"At the heart of the technology are silver nanowires, which form a conductive mesh," explains Glier. The silver wires are typically several tens of nanometers (millionths of a millimeter) thick and 10 to 20 micrometers (thousandths of a millimeter) long. The detailed X-ray

analysis shows that the structure of the nanowires in the polymer is not changed, but that the conductivity of the mesh even improves thanks to the compression by the polymer, as the polymer contracts during the curing process.

The [silver nanowires](#) are applied to a substrate in suspension and dried. "For cost reasons, the aim is to achieve the highest possible conductivity with as few nanowires as possible. This also increases the transparency of the material," explains Roth, head of the P03 measuring station at DESY's X-ray light source PETRA III, where the X-ray investigations took place. "In this way, layer by layer, a conductive path or surface can be produced." A flexible polymer is applied to the conductive tracks, which in turn can be covered with conductive tracks and contacts. Depending on the geometry and material used, various electronic components can be printed in this way.

In this paper, the researchers produced a flexible capacitor. "In the laboratory, we carried out the individual work steps in a layering process, but in practice they can later be completely transferred to a 3-D printer," explains Glier. "However, the further development of conventional 3-D printing technology, which is usually optimized for individual printing inks, is also essential for this. In inkjet-based processes, the print nozzles could be clogged by the nanostructures," notes Rübhausen.

In the next step, the researchers now want to test how the structure of the conductive paths made of nanowires changes under mechanical stress. "How well does the wire mesh hold together during bending? How stable does the polymer remain," said Roth, referring to typical questions. "X-ray investigation is very suitable for this because it is the only way we can look into the material and analyze the conductive paths and surfaces of the [nanowires](#)."

More information: Tomke E. Glier et al, Functional Printing of

Conductive Silver-Nanowire Photopolymer Composites, *Scientific Reports* (2019). [DOI: 10.1038/s41598-019-42841-3](https://doi.org/10.1038/s41598-019-42841-3)

Provided by Deutsches Elektronen-Synchrotron

Citation: Flexible circuits for 3-D printing (2019, April 29) retrieved 27 April 2024 from <https://phys.org/news/2019-04-flexible-circuits-d.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.