

Waste plastic converted into filtration membranes

October 21 2019



Bruno Pulido tests the efficiency of the team's synthetic membrane. Credit: KAUST

In a world that seems to be drowning in plastic bottles, recycling this waste into useful materials would help to reduce its environmental impact. KAUST researchers have now invented a way to turn plastic bottles into porous membranes that could be used as molecular filters in the chemical industry.

Roughly 40 percent of the [chemical industry](#)'s energy use goes into

separating and purifying chemicals in heat-intensive processes, such as distillation and crystallization. Using [porous membranes](#) to separate molecules from liquids could dramatically reduce that energy consumption. But most conventional membranes are not robust enough to withstand the sort of solvents used in industry, and alternative ceramic membranes tend to be very expensive.

The KAUST team turned instead to recycled poly(ethylene terephthalate) (PET). "PET is mechanically and chemically robust, making it useful for filtration and purification processes that require sterilization or cleaning with acids or bleach," says Bruno Pulido, Ph.D. student.

In 2016, global production of PET reached 50 million tonnes, accounting for about 9 percent of total plastic production. Roughly 30 percent of PET is used in the food industry, including single-use [plastic bottles](#). PET is typically "down-cycled" into lower-value products, such as clothing fabrics, so converting it into higher-value filtration membranes could provide a strong economic incentive to improve recycling rates.

To create their membranes, the researchers dissolved the PET and then used a different solvent to make the PET solid again, this time in the shape of a membrane instead of a bottle.

The team tested a wide range of different processing conditions and solvents and used an additive called poly(ethylene glycol) (PEG) to help form pores within the PET membranes. Changing the concentration and size of the PEG molecules helped to control the number and size of pores within the membrane, and thus fine tune its filtration properties.

After optimizing this process, the team measured how easily liquid flowed through the membranes and how well they separate molecules of different sizes. The best membranes had pore sizes that ranged from 35

to 100 nanometers wide, with pores covering up to 10 percent of the membrane's area; they also performed well at 100 degrees Celsius.

Pulido says that the membranes could be used as a support for thin layers of other filtration materials, such as those found in reverse osmosis membranes. "We're also working on the development of PET hollow fibers, a type of [membrane](#) with additional advantages over flat membranes," he adds.

More information: Bruno A. Pulido et al, Recycled Poly(ethylene terephthalate) for High Temperature Solvent Resistant Membranes, *ACS Applied Polymer Materials* (2019). [DOI: 10.1021/acsapm.9b00493](https://doi.org/10.1021/acsapm.9b00493)

Provided by King Abdullah University of Science and Technology

Citation: Waste plastic converted into filtration membranes (2019, October 21) retrieved 26 April 2024 from <https://phys.org/news/2019-10-plastic-filtration-membranes.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.
