

A single-digit-micrometer thickness wood speaker

November 18 2019, by Thamarasee Jeewandara





Schematic of the top-down approach to directly transform natural balsa into ultrathin wood films. (a) Left: schematic of the natural wood with its porous structure. Middle: the microstructure of the cellulose fibers in the wood cell walls. Right: the molecular chains of the cellulose fibers. (b) Left: schematic of the ultrathin wood with intertwined, compressed wood channels. Middle: the microstructure of the highly oriented cellulose fibers in the ultrathin wood cell walls. Right: hydrogen bond formation between the neighboring cellulose molecular chains. (c) Meter-long natural balsa wood with a thickness of 300 μ m made in the lab. Credit: Nature Communications, doi: 10.1038/s41467-019-13053-0

In a recent report on *Nature Communications*, Wentao Gan and a team of researchers at the departments of materials science and engineering in the U.S. have detailed the use of an ultrathin film of natural wood to create an audio speaker. The construct exhibited excellent mechanical properties including high tensile strength and increased Young's modulus . The properties of ultrathin thickness and exceptional mechanical strength allowed excellent acoustic properties with higher resonance frequency and greater displacement amplitude when compared to a commercial polypropylene diaphragm in an audio speaker. As proof of concept, Gan et al. directly used the ultrathin wood film as a diaphragm in a real speaker to emit music. The surfaces with excellent mechanical properties and acoustic performance were a promising candidate to build next-generation acoustic speakers.

Thin films in the scale of microns to nanometers in thickness have multifunctional applications in <u>solar cells</u>, <u>food packaging</u>, <u>water</u> <u>treatment</u>, <u>personal electronics</u> and as <u>acoustic sensors</u>. Acoustic membranes are typically very thin (micron-scale) and mechanically robust with a high modulus to allow a highly sensitive frequency response and high vibrational amplitude. Physicists and engineers have dedicated tremendous efforts in the past decades to develop a variety of



acoustic thin film materials based on <u>plastic</u>, <u>metal</u>, <u>ceramic</u> and <u>carbon</u> to enhance the quality of sound.

Plastic thin films are used ubiquitously in commercial speakers due to low cost and ease of manufacture, however, they impose an <u>enormous</u> <u>environmental impact</u> due to ineffective degradation. Metal, ceramic and carbon-based materials also demonstrate higher modulus compared to plastic film to improve the frequency response of the acoustic membrane. These components generally cost higher and require complex, energy consuming manufacturing processes. As a result, it is desirable to develop a biodegradable, acoustic thin film for green and cost-effective applications.

Morphology and chemical characterization of the wood films

Natural cellulose-based materials such as <u>bagasse</u>, <u>wood fibers</u>, <u>chitin</u>, <u>cotton</u>, <u>bacterial cellulose</u> and <u>lignocellulose</u> provide an environmentally friendly platform to manufacture thin films rapidly without using limited fossil resources. The natural structure of wood is an effective alternative for more scalable and mechanically robust cellulose films. Wood can be used as a scaffold to construct thin films in a top-down approach in a scalable and cost-effective process compared to bottom-up methods. Maintaining the alignment of cellulose fibers will allow robust mechanical properties in the resulting material. Wood is also renewable, biodegradable and environmentally sustainable compared to plastics and metal.

To build the ultrathin film with a thickness as low as 8.5 micrometers in the present work, Gan et al. partially removed lignin (delignification) and hemicellulose from natural balsa wood. They generated a highly porous material, which retained most of the cellulose in the cell walls,



followed by increasing the density of treated wood by hot pressing for a thickness reduction of 97 percent. The densely packed wood cell wall structure combined with highly aligned cellulose fibers, contributed to superior tensile strength and high Young's modulus. The research team used industry-based cutting methods to develop a meter-long natural balsa wood film in the lab to reveal the material's potential for large-scale manufacture via a top-down approach.

Mechanical properties of the wood films





Morphological characterization of wood films. (a) Photograph of the rotary cut natural wood. (b) SEM image of the natural wood, with a thickness of 300 μ m. Inset: top-view SEM image of the natural wood, showing its porous wood structure. (c) Photograph of the ultrathin wood. (d) SEM image of the ultrathin wood film, demonstrating its densified wood structure. Inset: Top-view SEM image of the ultrathin wood, revealing its collapsed wood cell walls. (e) The measured thickness of the ultrathin wood along its length at intervals of 5 μ m, indicating uniform film thickness. (f, g) SEM images of the ultrathin wood,



showing the aligned cellulose fibers. (h) Small-angle XRD pattern of the ultrathin wood, indicating the anisotropic alignment of the cellulose nanofibers. Credit: Nature Communications, doi: 10.1038/s41467-019-13053-0

Gan et al. cut the natural wood along its longitudinal direction to maintain the channel structure and observed the microscopic structures using scanning electron microscopy (SEM). The cellulose nanofibers in the ultrathin wood film remained highly oriented but more densely laminated compared to natural wood. X-ray diffraction (XRD) analysis indicated retention of the molecular alignment and crystal structure of the cellulose nanofibers, which was important for the material's mechanical properties.

To understand the material's mechanical properties, the research team conducted mechanical tensile tests. Ultrathin wood showed greatly improved mechanical behavior compared with natural wood, with increased fracture strength of up to 342 MPa and Young's modulus of 43.65 GPa. These values indicated an almost 20-times improvement in tensile strength and 35-times enhancement in Young's modulus compared to natural wood.

The scientists were keen to understand the underlying mechanisms. For this, they used SEM observations and demonstrated a porous microstructure with numerous wood channels in the natural wood slice after tensile tests. The feature made it easier to pull loosely assembled wood during tension; explaining the naturally low fracture strength observed. In contrast, wood cell walls within the synthetic ultrathin wood film formed hydrogen bonds between the firmly compressed cellulose nanofibers after densification; requiring higher energy to be pulled apart.





LEFT: Photograph of the speaker prototype made with the ultrathin wood film diaphragm. The electromagnetic forces act on the coil, allowing it to vibrate the diaphragm back and forth, in this manner translating the electrical signal into an audible sound. RIGHT: Mechanical properties of wood films. (a) Schematic of the tensile test along the longitudinal direction. (b) Corresponding tensile stress as a function of strain for the natural wood (blue line) and ultrathin wood film (red line). (c) Comparison of the tensile strength and Young's modulus of the natural wood and ultrathin wood film. Error bars represent standard deviation. (d, e) SEM images of the tensile fracture surface of the natural wood and ultrathin wood film. (f) Comparison of the tensile strength and Young's modulus of the ultrathin wood film with other widely used polymer and natural materials. (PA: Polyamide; PMMA: Poly (methyl methacrylate); PS: Polystyrene; PP: Polypropylene) (g–j) Photographs of the ultrathin wood film demonstrating its flexibility and various origami designs. (k, l) Photograph and SEM image of the natural wood after bending, showing its rigid wood structure. (m, n) Photograph and SEM image of the ultrathin wood film after bending, showing its excellent flexibility and folding performance. Credit: Nature Communications, doi: 10.1038/s41467-019-13053-0.



Acoustics and vibrational behavior of wood films

The high tensile strength and Young's modulus of the ultrathin film also exceeded typical plastic and natural biomaterials to validate its excellent mechanical properties. The exceptional flexibility and foldability allowed research teams to develop a variety of origami designs. In contrast, the brittle natural wood did not demonstrate such malleability. The foldability also highlighted potential uses of the ultrathin wood films for photonics, acoustic sensors and flexible electronics devices. The high Young's modulus and ultrathin nature of the wood film helped increase the resonance frequency and enhance displacement amplitude of the diaphragm vibration. These characteristics strongly suited the ultrathin wood film's applications as a diaphragm for acoustic transducers with a wide operation bandwidth, with high sensitivity for microphones and high sound pressure levels for speakers.

The new construct formed an <u>attractive alternative</u> to conventional polymer films, allowing the ultrathin wood film to become highly suitable for acoustic transducers with a wide operation bandwidth, high sensitivity and high sound pressure levels. To confirm the properties of increased resonance frequency and displacement, the team tested the frequency response of the ultrathin wood compared to a conventional polymer film. The results were highly desirable as high-performance acoustic transducers.





TOP: Acoustic properties of wood films. (a) Schematic of the vibrational frequency response measurement system. Insets: photographs of the commercial polymer diaphragm and ultrathin wood film. (b) The vibrational frequency response characteristics of the ultrathin wood film (50 μ m) and the commercial polymer (80 μ m) diaphragms. (c, d) The (0, 1) mode shapes of the polymer (80



 μ m) and ultrathin wood film (50 μ m) diaphragms, respectively. (e) Comparison of the corresponding displacement and first resonance frequency of the ultrathin wood film (50 μ m) and polymer (80 μ m) diaphragms. (f) The vibrational frequency response characteristics of the ultrathin wood film at different thicknesses. (g) The corresponding displacement and first resonance frequency as a function of the thickness for the wood films. BOTTOM: Wood speaker prototype. a Schematic of the wood speaker prototype. b Photographs of the speaker with the wood diaphragm. c The sound wave of the original song (Spain Matador March). d The recorded sound wave (Spain Matador March) of the speaker with the wood diaphragm. Credit: Nature Communications, doi: 10.1038/s41467-019-13053-0.

Gan et al. demonstrated promising applications of the ultrathin wood films as an acoustic transducer to assemble a miniature speaker. The prototype contained a wood diaphragm and a circuit board with a miniature speaker, containing a copper coil and permanent magnet. The setup facilitated <u>electromagnetic</u> forces to act on the coil and cause the diaphragm to vibrate back and forth. They translated the electrical signal into an audible sound, as a result of the air pressure caused by the diaphragm and recorded the audible sound of the speaker prototype using a microphone and soundwave, which they analyzed using <u>Adobe</u> <u>Audition CC</u>. The research team used the speaker to play a recording of the Spain Matador March. They expect to further improve the diaphragm structure design and precise assemblies within the existing industrial process. The sustainable technology can be translated into the manufacture of microphones, hearing aids and acoustic sensors.

In this way, Wentao Gan and colleagues developed and demonstrated an effective top-down strategy to engineer an ultrathin wood film less than 10 micrometers in thickness after subjecting natural wood to <u>delignification</u> and densification. They observed a unique microstructure for the ultrathin wood film with intertwined wood cell walls and aligned



cellulose nanofibers, which contributed to outstanding mechanical properties relative to improved tensile strength and Young's modulus. The research team achieved a high-performance acoustic transducer with increased resonance frequency and enhanced displacement amplitude. The green loudspeaker prototype generated music due to vibrations of the ultrathin wood diaphragm with wide-ranging acoustic applications of the material. The research team envision the technique will open additional functions and applications for strong film materials using sustainable and biodegradable natural resources to replace plastic, metal and ceramics.

More information: Wentao Gan et al. Single-digit-micrometer thickness wood speaker, *Nature Communications* (2019). DOI: 10.1038/s41467-019-13053-0

Stefan C. B. Mannsfeld et al. Highly sensitive flexible pressure sensors with microstructured rubber dielectric layers, *Nature Materials* (2010). DOI: 10.1038/nmat2834

Roland Geyer et al. Production, use, and fate of all plastics ever made, *Science Advances* (2017). <u>DOI: 10.1126/sciadv.1700782</u>

© 2019 Science X Network

Citation: A single-digit-micrometer thickness wood speaker (2019, November 18) retrieved 3 May 2024 from <u>https://phys.org/news/2019-11-single-digit-micrometer-thickness-wood-speaker.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.