

## Study recommends new approach to managing risk of earthquakes triggered by fracking

April 27 2020



A hydraulic fracturing drill site in southwestern Pennsylvania. Credit: Doug Duncan, USGS

Hydraulic fracturing for oil and gas production can trigger earthquakes, large and small. A new approach to managing the risk of these quakes could help operators and regulators hit the brakes early enough to



prevent nuisance and reduce the chance of property damage and injury.

The approach, developed by four Stanford University researchers and published April 28 in the *Bulletin of the Seismological Society of America*, centers on a calculation of the risk that shaking triggered by a given project will be felt in surrounding communities—long before earthquakes grow large enough to do harm.

Hydraulic fracturing, or fracking, involves pumping fluids at high pressure into wells drilled down into and across rock formations thousands of feet underground. The pressure creates small earthquakes that break the rock, forcing open existing fractures or creating new ones. Petroleum then flows more easily out of the cracked rocks and into the well. "The goal is to make many tiny earthquakes, but sometimes they are larger than planned," said study co-author William Ellsworth, a geophysics professor at Stanford's School of Earth, Energy & Environmental Sciences (Stanford Earth).

By taking the local risk of nuisance-level shaking as its starting point, the new strategy contrasts with the current common practice for managing fracking-related quakes based on size. Under a system known as a trafficlight protocol, operators have a green light to proceed as long as earthquakes remain relatively small. Larger earthquakes may require an operator to adjust or stop work. The system is widely used to manage hazards of fracking for oil and gas in the United States, Canada, China and Europe, and also for geothermal energy development in South Korea, Europe and the United States.

"Implicitly, I think regulators have had risk in the back of their mind," said study co-author Greg Beroza, a geophysics professor at Stanford. "But risk-based frameworks have not been used previously—perhaps because it requires a bit of extra analysis."



Earthquake size offers a rough proxy for how much damage can be expected, and it's a measure that regulators and operators can monitor in real time. The problem is quakes of the same size can present very different risks from one location to another due to differences in population density. "A project located in a virtually uninhabited area of west Texas would pose a much <u>lower risk</u> than a similar project located near a city," Ellsworth explained.

In addition, geological factors including <u>earthquake</u> depth, fault geometry and local soil conditions can influence how an earthquake's energy—and potential to do damage—becomes amplified or peters out as it travels underground. All of this context is key to honing in on a tolerable amount of shaking and establishing traffic-light thresholds accordingly.

"Areas such as Oklahoma, with buildings that were not designed to resist strong shaking, or areas that anticipate amplified shaking due to soft soils, can account for their community needs with this approach," said study co-author Jack Baker, a professor of civil and environmental engineering who leads the Stanford Center for Induced and Triggered Seismicity with Beroza, Ellsworth and Stanford geophysicist Mark Zoback.

The Stanford researchers developed mathematical techniques to account for the web of risk factors that shape the probability of an earthquake generating noticeable or damaging shaking in a specific location. They built upon these techniques to make a translation to earthquake magnitude. This allowed them to create guidelines for devising new traffic-light protocols that still use earthquake size to clearly delineate between the green, yellow and red zones, but with much more tailoring to local concerns and geology.

"If you tell me what exposure you have in a certain area—population



density, site amplification, distance to towns or critical infrastructure—our analysis can spit out numbers for green-, yellow- and red-light thresholds that are fairly well informed by real-world risks," said lead study author Ryan Schultz, a Ph.D. student in geophysics.

The analysis also makes it possible, he added, to start out with some level of risk deemed tolerable—say, a 50 percent chance of nuisance-level shaking at the nearest household—and calculate the maximum earthquake magnitude that would keep risk at or below that level. "This is about making it clearer what choices are being made," Schultz said, "and facilitating a conversation between operators, regulators and the public."

In general, the authors recommend setting yellow-light thresholds approximately two magnitude units below the red light. According to their analysis, this would result in 1 percent of cases jumping from the green zone straight to red. "If you stop the operation right at or before the threshold for damage, you're assuming you have perfect control, and often that's not the reality," Schultz said. "Often, the biggest earthquakes happen after you've turned off the pumps."

**More information:** *Bulletin of the Seismological Society of America* (2020). <u>doi.org/10.1785/0120200016</u>

Provided by Stanford University

Citation: Study recommends new approach to managing risk of earthquakes triggered by fracking (2020, April 27) retrieved 23 June 2024 from <u>https://phys.org/news/2020-04-approach-</u> earthquakes-triggered-fracking.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private



study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.