

3-D touchless interactive display detects finger humidity to change color



July 29 2020, by Thamarasee Jeewandara





Fabrication of interpenetrated hydrogel network BCP PC. (A) Schematic illustration of the fabrication processes of interpenetrated hydrogel network block copolymer photonic crystal (IHN BCP PC). (B) Surface morphology of a PS-b-QP2VP film swollen by ethanol, followed by being dried. Credit: Science Advances, doi: 10.1126/sciadv.abb5769

A novel three-dimensional (3-D) touchless interactive display can change color based on the distance of the user's finger from the screen by detecting subtle shifts in ambient relative humidity, according to a new study. The technology may find future applications in wearable electronics and <u>electronic skins</u> (e-skins) that artificially mimic human skin's ability to sense pressure, temperature, and humidity. While scientists have already developed a variety of interactive touch displays, most of these involve variations in the intensity of light emission or chromic reflection in response to a stimulus rather than changes in color, which can provide more striking and distinct visual feedback.

To develop a touchless interactive display based on changes in <u>structural</u> <u>color</u>, Han Sol Kang and colleagues in <u>materials science</u>, <u>nano</u> engineering and chemical engineering in the Republic of Korea and the U.S., designed a new display using chemically cross-linked, interpenetrated hydrogel network layers within photonic crystals that respond to changes in water vapor when a finger is moved from 1 to 15 millimeters from the surface. The process could shift the configuration of its surface structures to produce blue, green and orange colors. The researchers then demonstrated the possibility of easily transferring the photonic crystal-based film from one substrate to another by swapping it from a silicon surface to a printed one-dollar bill. By combining ionic liquid dopants (which alter a semiconductor's electrical properties) as



printing inks, the researchers note applications of the technology for printable and rewritable displays.

User-interactive displays (UIDs) facilitate the visualization of invisible information that can be sensed such as touch, smell and sound, with potential applications in wearable and patchable electronics suited for a futuristic hyperconnected society. The tremendous demand for electronic skin that can artificially mimic human skin to sense temperature, pressure and humidity has led to the development of a variety of human-interactive touch displays. A touch platform is in demand to visualize a stimulus without touch on 3-D interactive touchless displays. Kang et al. envision a stimuli-sensitive, low-power, reflective-mode, visible-range structural color (SC) of a photonic crystal (PC) to satisfy the engineering requirements of a <u>user-interactive 3-D</u> touchless display. The scientists developed a printable 3-D touchless interactive display using a hygroscopic ionic liquid ink with facile structural color variation relative to humidity. As proof of concept, they showed 3-D position-sensing of <u>water vapor</u> emanating from a human finger (humidity) for touchless display from finger to film, with emerging applications in wearable electronics.





Interpenetrated hydrogel network block copolymer photonic crystal. (A) Schematic illustration of BCP PC display with multiorder reflection SCs. Visible



range SC of BCP PC is realized with the interpenetrated hydrogel network (IHN) of PEGDA in PQ2VP domains. By using nonvolatile ionic liquid of either EMITFSI or LiTFSI in IHN BCP PC, richer SCs are developed by mixing of multiorder reflection SCs. (B) Ultraviolet-visible (UV-vis) spectra of IHN BCP PC films on the glass as a function of UV exposure time. (C) Plot of the wavelength at maximum reflection as a function of UV exposure time from 10 to 60 s. (D) Photographs of IHN BCP PC film on glass substrates as a function of UV exposure time. The right end photograph shows its maximum reflection in near infrared (NIR) regime. (E) Photographs of a solid-like flexible IHN BCP PC on a black paper. Photo credit: H.S.K., Yonsei University. Credit: Science Advances, doi: 10.1126/sciadv.abb5769

Developing an interpenetrated hydrogel network block copolymer photonic crystal (IHN BCP PC)

The team used self-assembled 1-D block copolymer (BCP) photonic crystals (PC) whose layered periodic microstructure developed spontaneously upon film formation. They then developed chemically cross-linked interpenetrated hydrogel network (IHN) layers in a BCP PC microdomain. Kang et al. controlled the amount of interpenetrated hydrogel network in the construct using UV irradiation to control its structural color (SC) across the full visible range. Using photographs of the engineered interpenetrated hydrogel network block copolymer photonic crystals (IHN BCP PCs), they showed the irradiationdependent variation of SC. The polymer film was pseudoelastic (the material recovered completely after unloading large strains) with excellent mechanical robustness, flexibility and without sticky, gel-like viscoelasticity on the upper surface to make it suitable for solid-state sensing.





Calculation of IHN BCP PCs with red, green, and blue structural colors. Finitedifference time-domain (FDTD) simulation results of IHN BCP PCs with their SCs of red, green, and blue. Credit: Science Advances, doi: 10.1126/sciadv.abb5769

Characterizing the solid-state IHN BCP PCs



Kang et al. extensively characterized the solid-state construct using grazing incident small angle X-ray scattering (GISAXS) and transmission electron microscopy (TEM). The results showed the development of highly ordered 1-D photonic crystal structures and their calculated inplane lamellae were consistent with <u>finite-difference time-domain</u> (FDTD) simulations. For cross-sectional transmission electron microscopy, they used cross-sectioned samples of the mechanically robust film via <u>focused ion beam milling</u> and noted the different layers of the material lamellae.

The TEM images of BCP films showed <u>screw dislocations</u> (defects in crystals) distributed across the sample surface to facilitate the transport of liquid and <u>oligomeric agents</u> into the BCP films. The BCP film allowed water molecules to diffuse through screw dislocations to facilitate humidity based touchless sensing. The team obtained additional mechanical properties including the effective modulus of the IHN BCP PCs using <u>nanoindentation</u>. The pseudoelastic material had an effective elastic modulus approximating 5.3 GPa—as expected and similar to those observed for conventional glassy polymers.





Printable and rewritable SCs on IHN BCP PC. (A) Schematic of inkjet printing on IHN BCP PC film with ionic liquid (IL) ink. (B) Photograph of an IL inkprinted IHN BCP PC film with different concentrations. (C) Computerprocessed image of the part of a one dollar bill in black and white contrast. (D) Photograph of the SC image printed by adjusting the concentration of the IL ink



based on the contrast image in (C). (E) Optical microscope image of lines printed with IL on an IHN BCP PC film, which shows a resolution of the SC lines of approximately 50 µm. Photographs of IL ink-printed SC images of IHN BCP PCs on (F) a conventional paper and (G) glass substrate. (H) Photograph of an IL inkjet-printed image of an IHN BCP PC film arising from multiorder reflection SCs in visible range. (I) UV-vis spectra of an IHN BCP PC film printed with IL (red), followed by the removal of the IL by a neat PEGDA pad (black). (J) Maximum reflection wavelength values with repetitive IL writing and erasing processes. (K) Photographs of different IHN BCP SC images with repetitive printing and erasing of IL ink. An IHN BCP SC image (step 1) inkjetprinted with IL on an IHN BCP PC film, followed by removal of IL with a neat PEGDA pad. The printing and erasing process is repeatable (steps 2 and 3). Photo credit: H.S.K., Yonsei University. Credit: Science Advances, doi: 10.1126/sciadv.abb5769

Obtaining full color display and developing a user-interactive 3-D touchless screen

To obtain a full color display, Kang et al. used an <u>inkjet printer</u> for direct deposition of an ink known as <u>L-ethyl-3-methylimidazolium</u> <u>bis-(trifluoromethylsulfonyl)-imide</u>, abbreviated EMIMTFSI, on an IHN BCP PC film. The color of the film depended on the amount of EMIMTFSI deposited in a given region. The inkjet printer only required a single ink for deposition on the IHN BCP PC film, which markedly differed from a commercial inkjet printer with red, green, and blue dye inks. Kang et al. produced a given colored image by first programming the appropriate color information into a black/gray/white contrast. As proof of concept, they converted a U.S. dollar bill to a black and white contrast using software, and reconstructed the full color structural color image using EMIMTFSI inkjet printing on an IHN BCP PC film.







3-D touchless BCP structural color sensing display. (A) Schematic illustration of humidity-sensitive SC change in an LiTFSI-doped IHN BCP PC. (B) Schematic of two-terminal parallel-type 3D touchless sensing display with an LiTFSI-doped IHN BCP PC. Height 1 (h1) is higher than height 2 (h2). (C) Variation of relative humidity as a function of the finger-to-PC distance. (D) Photographs of LiTFSI-doped IHN BCP PCs in various relative humidity conditions from 40 to 90 RH%. (E) Photograph showing SC of an LiTFSI-doped IHN BCP PC when a finger is close to the surface. (F) Capacitance change of a 3D touchless sensing display with an LiTFSI-doped IHN BCP PC upon variation of finger-to-PC distance from 15, 9, 5, and 3 mm. (G) Variation in capacitance of the 3D touchless sensing display upon repetitive alteration of the finger-to-PC distance. Schematic (H) and photograph (I) of arrays for 3D touchless sensing displays. (J) 3D capacitance change map obtained from the arrays of 3D touchless sensing displays with a finger close to the surface of the arrays. Photo credit: H.S.K., Yonsei University. Credit: Science Advances, doi: 10.1126/sciadv.abb5769

For further applications of the IHN BCP PC display, Kang et al. used another hygroscopic ionic liquid named

bis(trifluoromethylsulfonyl)amine lithium salt (abbreviated LiTFSI). Upon diffusion of this ionic liquid into the material, the structural color of the photonic crystal became sensitive to environmental humidity. The LiTFSI allowed association with water molecules for structural color variations to occur across the visible range as a function of humidity. The absorbed water could be diffused out in a reversible process. The setup allowed the human finger with natural humidity approximating 90 percent to be an excellent source to modulate the structural color of the display film, which the team confirmed experimentally. The 3-D touchless sensing display worked successfully under multiple sensing events with different finger-to-<u>photonic crystal</u> distances. Increased capacitance due to water uptake approximated a response time of 20



seconds and the reversible change in structural color lasted 55 time cycles.

In this way, Han Sol Kang and colleagues demonstrated a userinteractive 3-D touchless sensing <u>display</u> based on block copolymer photonic crystals with interconnected hydrogel networks (abbreviated IHN BCP PCs). The engineering technique allowed for mechanically soft and robust full-visible-range structural colors on a film with an effective modulus. The team combined the film with various ionic liquid printing inks to create printable and rewritable displays for 3-D touchless sensing through varying capacitance and structural color changes, to demonstrate a new approach for solid-state sensors and 3-D touchless displays.

More information: Han Sol Kang et al. 3D touchless multiorder reflection structural color sensing display, *Science Advances* (2020). DOI: 10.1126/sciadv.abb5769

Wei Gao et al. Fully integrated wearable sensor arrays for multiplexed in situ perspiration analysis, *Nature* (2016). <u>DOI: 10.1038/nature16521</u>

André C. Arsenault et al. From colour fingerprinting to the control of photoluminescence in elastic photonic crystals, *Nature Materials* (2006). DOI: 10.1038/nmat1588

© 2020 Science X Network

Provided by Science X Network

Citation: 3-D touchless interactive display detects finger humidity to change color (2020, July 29) retrieved 10 May 2024 from https://phys.org/news/2020-07-d-touchless-interactive-finger-humidity.html



This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.