

A Plug-and-play approach to integrated nanoacoustics

November 20 2020



Top-left : SEM image of the micropillar optophononic resonator, and fibered device. Top-right: Acoustic spectrum of the nanomechanical resonator. Bottom: time trace measured using a fibered pump-probe coherent phonon generation scheme. Credit: Centre for Nanoscience and Nanotechnology



From taut strings vibrating in musical instruments to micro-electromechanical systems for optoelectronics, vibrations cover an extensive range of applications. At the nanoscale, the study of mechanical vibrations poses several challenges and opens up a virtually infinite playground for nanotechnologies. Exciting potential benefits of controlled vibrations in the GHz-THz frequency range include better thermal transport management, novel quantum acoustic technologies, improved optoelectronic devices, and the development of novel nanoscale sensors.

However, the standard optical techniques used to generate, detect and manipulate these vibrations suffer from mechanical stability issues, limited reproducibility of experimental results, and usually require large optical power densities that many samples do not withstand. Researchers from the Center de Nanosciences et de Nanotechnologies—C2N (CNRS / University Paris Saclay) and Quandela SAS, have proposed a novel strategy that simultaneously solves these problems by integrating fibered systems into pump-probe experiments, replacing complex optical alignments protocols with a plug-and-play device.

The researchers tested the new approach with a single-mode fiber glued onto an opto-phononic micropillar. They realized pump-probe experiments without the need for any further optical alignment beyond plugging fiber connectors by spatially overlapping the micropillar's optical mode with the core of the fiber and gluing them together. A critical requirement in pump-probe experiments is to detect the probe beam exclusively and reject any contribution from the pump beam on the optical detector. The usual way to achieve this condition is to use cross-polarized pump and probe beams. To overcome the polarization rotation due to the single-mode fiber, the researchers combined their fiber approach with optical polarization control, resulting in a fibered



cross-polarization scheme. The fibered device allows stable pump-probe signals for more than forty hours and can operate at very low excitation powers below 1mW to detect vibrations at the nanoscale. The work was published in *Applied Physics Letters*.

The fibered optophononic micropillar constitutes a much-improved platform for reproducible plug-and-play <u>pump-probe</u> experiments in individual microstructures. It lifts the necessity of complex optical setups to couple into microstructures. In addition, the demonstrated stability and the convenience of a fiber connector as the only necessary element to interface a sample with an existing experimental setup make it transportable and allows obtaining consistent measurements from the same device at any laboratory in the world. These results demonstrate the synergy present at the C2N, where united efforts of internationally leading nanofabrication facilities, research groups and private companies create a remarkable impact in the science world.

More information: O. Ortiz et al. Fiber-integrated microcavities for efficient generation of coherent acoustic phonons, *Applied Physics Letters* (2020). DOI: 10.1063/5.0026959

Provided by Centre for Nanoscience and Nanotechnology

Citation: A Plug-and-play approach to integrated nanoacoustics (2020, November 20) retrieved 15 May 2024 from <u>https://phys.org/news/2020-11-plug-and-play-approach-nanoacoustics.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.