

Activated carbon increases cryocooler efficiency

April 6 2021



4 K pulse tube cryocooler developed by researchers at the Technical Institute of Physics and Chemistry, Chinese Academy of Sciences. Credit: Liubiao Chen/University of Chinese Academy of Sciences

Cryocoolers are ultracold refrigeration units used in surgery and drug development, semiconductor fabrication, and spacecraft. They can be tubes, pumps, tabletop sizes, or larger refrigerator systems.



The regenerative heat exchanger, or regenerator, is a core component of cryocoolers. At temperatures below 10 kelvins (-441.67 degrees Fahrenheit), performance drops precipitously, with maximum regenerator loss of more than 50%.

In their paper, published in *Applied Physics Letters*, researchers at the University of Chinese Academy of Sciences used superactivated <u>carbon</u> particles as an alternative regenerator material to increase cooling capability at temperatures as low as 4 kelvins.

In most cryocoolers, a compressor drives room <u>temperature</u> gas through the regenerator. The regenerator soaks up heat from the compression, and the cooled gas expands. The oscillating ultracold gas absorbs the heat trapped in the regenerator, and the process repeats.

Nitrogen is the most commonly used gas in cryocoolers. But for applications requiring temperatures below 10 kelvins, such as space telescope instruments and magnetic resonance imaging systems, helium is used, because it has the lowest boiling point of any gas, enabling the coldest attainable temperatures.

However, helium's high specific heat (the amount of heat transfer needed to change the temperature of a substance) results in large temperature fluctuations during the compression and expansion cycle at low temperatures, which seriously affects cooling efficiency.

To address this problem, researchers replaced the regenerator's conventional rare-earth metals with <u>activated carbon</u>, which is carbon treated with <u>carbon dioxide</u> or superheated steam at high temperatures. This creates a matrix of micron-size pores that increases the carbon's <u>surface area</u>, enabling the regenerator to hold more helium at low temperatures and remove more heat.



The researchers used a 4 kelvins Gifford-McMahon cryocooler to test the helium adsorption capacity in superactivated <u>carbon particles</u> with a porosity of 0.65 within varying temperature ranges of 3-10 kelvins.

They found when they filled the regenerator with 5.6% of carbon with diameters between 50 and 100 microns, the obtained no-load temperature of 3.6 kelvins was the same as using precious metals. However, at 4 kelvins, cooling capacity increased by more than 30%.

They confirmed improved performance by placing coconut shellactivated carbon into an experimental pulse tube they built and using a thermodynamic calculation model.

"In addition to providing increased cooling capacity, the activated carbon can serve as a low-cost alternative to <u>precious metals</u> and could also benefit low-temperature detectors that are sensitive to magnetism," author Liubiao Chen said.

More information: "Study on the use of porous materials with adsorbed helium as the regenerator of cryocooler at temperatures below 10 K" *Applied Physics Letters* (2021). aip.scitation.org/doi/10.1063/5.0044221

Provided by American Institute of Physics

Citation: Activated carbon increases cryocooler efficiency (2021, April 6) retrieved 15 May 2024 from <u>https://phys.org/news/2021-04-carbon-cryocooler-efficiency.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.