

More sustainable mortars and concrete with optimal thermal and mechanical efficiency

June 10 2021



A foundation built to scale for studying geothermal energy. Credit: UPV/EHU

The consumption of raw materials has increased notably in industry in general, and in the construction industry in particular, amidst growing concerns over sustainability issues. Concrete and mortar are the most commonly used materials in construction, and many studies are currently



underway to try to reduce the harmful effects of their manufacture. Concrete and mortar are made by mixing water, sand, cement and aggregates.

"The main problem is the amount of cement used to produce this type of material; cement manufacturing uses a huge amount of energy and natural resources, which implies a high level of CO₂ emissions. Diverse studies are underway aimed at reducing the quantity of cement required. We are working to replace cement and aggregates (sand or gravel) with non-natural materials, in order to reduce the use of natural resources and optimize the mechanical and thermal properties of the materials produced," explains Roque Borinaga Treviño, a researcher at the UPV/EHU's Department of Mechanical Engineering.

To this end, the research team is analyzing by-products from different industrial processes, which enable the mortars and concretes produced to be used for different functions, depending on the mechanical and thermal properties they acquire. "The aim is to reduce as much as possible the volume of industrial by-products that end up in landfill sites, and to reuse these products in accordance with the dictates of the circular economy," claims Dr. Borinaga. Recently, the research team has explored three different by-products in three different areas.

Specific cases

Firstly, they have studied the possibility of using industrial metal waste as a reinforcement in concrete or mortar, analyzing mortars reinforced with brass fibers from electrical discharge machining. Secondly, and linked to this avenue of research aimed at reducing the amount of cement required, they have explored the use of lime mud waste from the paper industry, obtaining good results in terms of thermal conductivity and finding that the resulting material is adequate for use in radiant floor heating systems. And finally, they have used furnace slag as an



aggregate. "The thermal conductivity of sand extracted from electric arc furnaces is low, making it a good option for insulation purposes," explains Dr. Borinaga.

Although they are studying many different types of materials, what they are doing is basic research. "Ours is the first step in researching these materials. Industrial by-products and waste are not particularly homogeneous, meaning that they vary greatly in accordance with their origin. Therefore, the first step is to analyze the properties bestowed by each specific type of waste. It is important to conduct these analyses with a large amount of <u>waste</u> with different origins, and to compare the results in order to determine whether or not the materials are suitable for use in manufacturing," he concludes.

More information: R. Borinaga-Treviño et al. Lime mud waste from the paper industry as a partial replacement of cement in mortars used on radiant floor heating systems, *Journal of Building Engineering* (2021). DOI: 10.1016/j.jobe.2021.102408

Provided by University of the Basque Country

Citation: More sustainable mortars and concrete with optimal thermal and mechanical efficiency (2021, June 10) retrieved 20 May 2024 from <u>https://phys.org/news/2021-06-sustainable-mortars-concrete-optimal-thermal.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.