

Although counter-intuitive, noise can help image reconstruction

August 20 2021, by Zhang Nannan



(a). The coherent image of a resolution chart is scattered by a rotating diffuser, and then the diffusive image is sent onto bulk NLCs. Nonlinear output from the NLCs is imaged onto a camera; (b). Coherent image; (c). diffusive image. Credit: XIOPM

People are always eager to obtain clear imaging results through some turbid media, so a variety of methods have been developed to filter out noise and strive to improve the quality of imaging, as if noise is born as



the evilest enemy.

However, there is always a gap between intuition and truth. In some cases, <u>noise</u> does not degrade the <u>image quality</u>, rather can be used to improve it. For example, the stochastic resonance (SR) method is proved effective to recover the noise-hidden images.

A team led by Prof. Liu Hongjun from the Xi'an Institute of Optics and Precision Mechanics (XIOPM) of the Chinese Academy of Sciences (CAS) demonstrated a SR-based <u>image reconstruction</u> via magnetooptical molecular reorientation in bulk Nematic Liquid Crystals (NLCs) theoretically, which was made of affordable functional materials without dimensional restriction. Result was published in *Optics Express*.

In their research, the diffusive images were effectively recovered by reasonably optimizing the input light intensity, the magnetic field direction, and the correlation length.

According to the researchers, the secret of using noise to enhance the quality of image reconstruction is that the underlying signals are reinforced by coupling with scattering noise under reorientation-induced self-focusing nonlinearity, where noise plays a positive role. However, incoherent modulation instability occurs and the enhancement process of signals is destroyed under strong self-focusing nonlinearity.

They also studied the quality of image reconstruction with different magnetic field angles. The gain curve versus the magnetic field angle first increases, and then decreases. The NLCs have the maximum reorientation response to the light field at the angle of about 50 degrees.

These results suggest a potential method to recover the noisy images and promote the application of NLCs in the area of image processing.



More information: Yongbin Zhang et al, Magneto-optically reorientation-induced image reconstruction in bulk nematic liquid crystals, *Optics Express* (2021). DOI: 10.1364/OE.425642

Provided by Chinese Academy of Sciences

Citation: Although counter-intuitive, noise can help image reconstruction (2021, August 20) retrieved 30 April 2024 from <u>https://phys.org/news/2021-08-counter-intuitive-noise-image-reconstruction.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.