

Cross-linked hole transport layers for highefficiency perovskite tandem solar cells





Schematic of perovskite/perovskite and perovskite/silicon tandem solar cells. Credit: ©Science China Press

The power conversion efficiency (PCE) of single-junction perovskite solar cells (PSCs) has increased remarkably from 3.8% to 25.2% in just a decade. As the rapid development of PCE has been approaching the limit of its theoretical efficiency, fabricating tandem solar cells by combining subcells with different bandgaps offers an avenue to go beyond the Shockley-Queisser limits of single-junction solar cells.



The tandem devices utilize different parts of the solar spectra using subcells with different bandgaps to reduce the thermal loss of photogenerated carriers. Due to the tunable bandgap, high absorption coefficient and low fabrication cost, metal halide perovskites are promising candidates for tandem devices.

However, the efficiency of perovskite-based tandem <u>solar cells</u> is largely limited by wide-bandgap top-cells which typically possess a large opencircuit voltage (V_{OC}) loss. The severe nonradiative charge recombination at the interface between perovskite and hole transport layer (HTL) is a key factor leading to the large V_{OC} loss.

Recently, research group of Prof. Hairen Tan from Nanjing University has used the cross-linked organic small molecule VNPB as the HTL for wide-bandgap perovskite solar cells. A V_{OC} increase of nearly 50 mV was successfully obtained for wide-bandgap solar cells with bandgaps of 1.6 eV, 1.7 eV and 1.8 eV. Compared with the control device using PTAA polymeric HTL, the perovskite films deposited on VNPB have larger grain size and better crystallinity. VNPB enables faster charge extraction and reduces defect density at the HTL/perovskite interface.

Density functional theory (DFT) calculation shows that the closer contact between VNPB and perovskite increases the defect formation energy and decreases the defect density, thus effectively reducing the non-radiative recombination of carriers. Finally, the PCEs of perovskite/perovskite and perovskite/silicon tandem solar <u>cells</u> using VNPB as HTL reach 24.9% and 25.4%, respectively.

This work shows that cross-linkable small molecules are promising for high-efficiency and cost-effective <u>perovskite tandem</u> photovoltaic devices.

More information: Yurui Wang et al, Cross-linked hole transport



layers for high-efficiency perovskite tandem solar cells, *Science China Chemistry* (2021). DOI: 10.1007/s11426-021-1059-1

Provided by Science China Press

Citation: Cross-linked hole transport layers for high-efficiency perovskite tandem solar cells (2021, September 6) retrieved 17 July 2024 from <u>https://phys.org/news/2021-09-cross-linked-hole-layers-high-efficiency-perovskite.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.