

CO2 separation by special membranes

November 12 2021, by Barry Van Der Meer



Chemical engineer Menno Houben developed a new type of membrane that is more successful at removing CO2 from combustion gases under high pressure. Credit: Eindhoven University of Technology

Worldwide, CO_2 -emissions must be reduced drastically and one way is separation of CO_2 from industrial waste streams. These membranes do not function properly at high pressure conditions however. Chemical



engineer Menno Houben found the cause and optimized special membranes that allow separating CO_2 at high pressure. Friday November 19th he will defend his Ph.D. thesis at the department of Chemical Engineering and Chemistry.

To prevent the worst impacts of climate change, the amount of atmospherical CO_2 should be reduced. CO_2 could be separated from natural gas and biogas, but also from industrial waste streams, to minimize atmospheric pollution. Diverse polymeric membranes are already developed for this kind of separation. However, these membranes do not function properly at high pressure conditions and therefore Ph.D.-student Menno Houben investigated how a more efficient capture of CO_2 could be realized.

Membranes without pores

If you want to <u>separate</u> CO_2 using a <u>membrane</u>, you need <u>pressure</u> difference, Houben explains. "At a higher pressure, subsequently more gas will flow through the membrane. You might think of a kind of coffee filter containing microscopic pores, but the membranes we use for gas separation are quite different. They do not contain any pores and are often called dense membranes."

"These membranes can have a very high separation efficiency, but when the gas pressure goes up, problems arise and suddenly they are a lot less efficient. Tricky, because you need high pressure to keep productivity high. And natural gas, for example, is also under a high pressure in the ground."

Swelling membrane

According to Houben, the problems arise from plasticization, the



swelling of the membrane due to the absorption of a lot of CO_2 . At higher pressures in particular, the membrane swells quickly and therefore functions much less well.

In addition, CO_2 under high pressure is in the supercritical phase. In this manifestation, the distinction between gas and liquid phase has disappeared and it has unique properties. Supercritical CO_2 only occurs at relatively high temperature and pressure, precisely conditions in which separation membranes quickly plasticize.

Heat treatment

Houben investigated the plasticization process at <u>molecular level</u> and found that especially at supercritical conditions, the membrane's performance is mainly determined by the balance between the liquid properties of CO_2 and plasticization.

"We also saw that stable membranes are a lot more resistant to plasticization and so the membrane remains well separated for longer. We obtained these stable membranes in three different ways: by mixing polymers, a heat treatment and by chemically cross-linking the membranes. All methods proved effective, but the membranes that had undergone <u>heat treatment</u> gave the most favorable properties."

"This allowed us to make a stable membrane that works well at high pressures and does not plasticize as quickly. Now admittedly only on a lab scale, but hopefully these insights can start to be used in the development of new stable membranes for high-pressure applications."

Menno Houben will defend his thesis "Critical aspects of high-pressure CO2-induced plasticization in polyimidemembranes" on Friday, November 19.



Provided by Eindhoven University of Technology

Citation: CO2 separation by special membranes (2021, November 12) retrieved 23 May 2024 from <u>https://phys.org/news/2021-11-co2-special-membranes.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.