

Finding the way: Examining flood evacuation route choices in Kampong settlements in Indonesia

November 8 2022





Path blocked by building

The figure shows the aggregate number of dwellers' evacuation route choice in Kampong Terban and Bener (left picture) and the Space syntax results of Normalized Angular Choice at 400 m radii. The thick lines represent the aggregate number of evacuees traveling on a certain path segment. They indicate



that a majority of riverbank kampong dwellers evacuate through the shortest and straightest route with the least angular deviation. Credit: Hitoshi Nakamura from SIT, Japan

Emergency evacuation is an important disaster response action. Recent frequent instances of natural and man-made disasters necessitate effective evacuation planning. It involves factors such as road network properties, street geometry, path risk, and environmental information. Such plans are difficult to implement because of the complex psychological reactions of the affected people during an emergency. For instance, in flood disaster preparation, the responsiveness and resilience of a community at risk are crucial. However, little is known about how informal settlement dwellers negotiate their surroundings during evacuation.

Recently, Mr. Irsyad Adhi Waskita Hutama (a Doctoral Program student) and Professor Hitoshi Nakamura of Shibaura Institute of Technology, Japan, analyzed the dynamic interaction between human characteristics, path risk elements, and path network configuration in constructing flood <u>evacuation</u> route choices. The study was conducted in Terban and Bener, which are two urban riverbank kampongs (villages) in Yogyakarta, Indonesia. Their findings were published in the *International Journal of Disaster Risk Reduction*.

Prof. Nakamura reveals his motivation behind the research: "Riverbank kampongs in Indonesian cities have grown spontaneously. Their residents typically include <u>low-income</u> and marginalized people who lack disaster prevention infrastructure. I am interested in how such communities can undertake disaster risk management and mitigate future disasters. A study on evacuation measures in riverbank kampongs will indicate reliable life-saving actions in response to flood, earthquake,



and other disasters."

The researchers applied a mixed-method approach. First, they collected extensive data regarding path risk factors through walking evacuation simulations recorded on video. Next, walking interviews were conducted to gain exploratory information on individual capacity and decisionmaking. Finally, the researchers performed computational path network analysis using the Space syntax model. The results of these analyses were combined to paint the overall picture.

Kampong Terban 600 cm 600 cm Accessibility High Bolected evecuator route	ment A Se Totoropysie Patra ng + riformal extension Patra Patra Patra Patra	gment B	Segment C
Street properties	Segment A	Segment B	Segment C
NACH local	1.33 (high)	0.94 (middle)	1.31 (high)
Presence of evacuation sign	No	Yes	Yes
Height/width ratio	1:3	1:2, 8	1:1, 5
Street-facing building	100%	80%	100%
Path disturbances	Narrow, motorcycle parking, informal house extension, significantly inundated when flooding	Slippery when raining, slope path, and stairs type	Motorcycle parking
Kampong Terban P Accessibility Accessibility Belected evecuation route	sgment D Cri So ori 20	are the second s	Segment F
Street properties	Segment D	Segment E	Segment F
NACH local	0.88 (low)	1.40 (high)	1.35 (high)
Presence of evacuation sign	Yes	Yes	Yes
Height/width ratio	1:8, 8	1:1	1:1, 3



Analysis of path risk elements (external factors) from the perspective of evacuees through the walking evacuation simulation with video. The path risk elements of evacuation route constitute the built-form element such as street network configuration, presence of evacuation sign, spatial enclosure, streetfacing building, and path use and disturbances. In summary, this figure depicts the complexity of evacuation route choice which can be effectively analyzed using a mixed-method approach to demonstrate the influence of the interplay of internal and external factors on evacuation behavior in urban riverbank kampongs. Credit: Hitoshi Nakamura from SIT, Japan

Their findings suggest that riverbank kampong dwellers select evacuation routes based on their individual capacity and the safety performance of path design. Many of them rely on safety perception instead of following spatial logic. Consequently, their evacuation route decisions might be compromised. Moreover, the walking interview revealed that men had higher spatial legibility and path safety perception than women in both <u>case studies</u>.

Further, the researchers juxtaposed the Space syntax results with the walking evacuation simulation. The individual evacuation route selection was found to be highly related to the "normalized angular choice at local radii."

This implies that a majority of residents prefer to walk on the straightest route—with the least angular deviation—to reach the assembly points. Furthermore, in agreement with the personal interviews, the residents have different capabilities to walk on the straightest evacuation path. In particular, physical capacity, gender, and age affected people's decisions in negotiating path risk elements and accommodating the safest travel.

Prof. Nakamura points out the long-term implications of the study. "Our study attempts to bridge the research tradition on disaster studies that



focus on the morphological approach on one hand, and a humancentered approach on the other. Its findings indicate a policy insight that includes routine disaster prevention actions consistent with the sociospatial profile of the kampong's marginalized. The enhancement includes not only structural measures such as human-sensitive urban design, readability of evacuation routes through signage, and the provision of evacuation infrastructure but also community preparedness. These measures should be included in kampong upgrading and slum alleviation policies aimed at achieving the SDGs."

Overall, the study highlights the use of mixed-method approaches and emphasizes the need to consider the human-centered perspective in effective flood emergency evacuation planning for informal riverbank settlements.

More information: Hutama A.W. Irsyad et al, Flood disaster evacuation route choice in Indonesian urban riverbank kampong: Exploring the role of individual characteristics, path risk elements, and path network configuration, *International Journal of Disaster Risk Reduction* (2022). DOI: 10.1016/j.ijdrr.2022.103275

Provided by Shibaura Institute of Technology

Citation: Finding the way: Examining flood evacuation route choices in Kampong settlements in Indonesia (2022, November 8) retrieved 23 June 2024 from https://phys.org/news/2022-11-evacuation-route-choices-kampong-settlements.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.