

NASA Armstrong develops tech to bring space launch to any airport

November 3 2022, by Jim Skeen



This artist's concept drawing shows how the Towed-Glider Air Launch System, or TGALS, would work. A business jet-class aircraft would tow a remotely piloted glider with a launch vehicle mounted underneath it. Once released at about 40,000 feet, the glider uses its own small rocket motor to execute a pull-up maneuver, releasing the launch vehicle for ignition at an elevated flight path

angle. Credit: NASA

A NASA-developed space launch system is attracting interest from companies that need to launch satellites in orbit. This same launch system could also develop high-flying, ultra-fast aircraft for national defense.

The Towed-Glider Air Launch System, or TGALS, is a low-cost, [flexible approach](#) for putting satellites and other payloads into space. Developed at NASA Armstrong Flight Research Center in Edwards, Calif., the innovative TGALS technique uses a low-cost glider to carry rockets and release them at the optimum place in the sky.

The TGALS technique uses a business jet-class aircraft to tow a remotely piloted glider with a [launch vehicle](#) mounted underneath it. Once released at about 40,000 feet, the glider uses its own small rocket motor to execute a pull-up maneuver, releasing the launch vehicle for ignition at an elevated flight path angle. After release, the glider returns to the airfield to be stored for the next mission.

"I think one of the big selling points is the flexibility for launch windows and launch locations around the world," said Brian Boogaard, Technology Transfer Administrator at NASA Armstrong. "There's only a handful of rocket pads where you launch a rocket, but you could fly the TGALS system anywhere there's an airport. There's a lot of flexibility that comes with it."

In addition to the launch flexibility, TGALS can carry launch vehicles that are 30% heavier compared to air-launched vehicles and 70% heavier than those using ground-based rockets.

The system offers improved safety by not having an on-board aircrew in an aircraft attached to or near a potentially explosive rocket.

NASA Armstrong researchers conducted proof-of-concept demonstration flights using radio-controlled one-third scale models of both glider and rocket. The tests included using a 27-foot- wingspan, twin-hulled glider home-built at NASA Armstrong and towed by the small DROID—for Dryden Remotely Operated Integrated Drone—unmanned aircraft.

Researchers also conducted studies and simulations of a glider capable of carrying an 80,000-pound rocket.

Transferring technology to American industry

One company, Fenix Space, Inc. in San Bernardino, signed a [licensing agreement](#) with NASA to use the TGALS technology. NASA Armstrong is in talks with a second company also interested in the technology.

While there is interest from private companies in licensing TGALS technology, it could be a valuable tool for the Department of Defense as it expedites its hypersonic research, said Ben Tomlinson, NASA Armstrong Technology Transfer Officer.

TGALS could pair up with Sky Range, a program that uses high-altitude, long duration flight Global Hawk aircraft to provide telemetry for hypersonic research missions, Tomlinson said. Sky Range provides greater flexibility and reduced costs for hypersonic missions by replacing an aging fleet of ships deployed across the Pacific Ocean.

"TGALS is a good marriage with Sky Range," Tomlinson said. "Now we can do cool stuff with hypersonic vehicles again. TGALS is a cost-effective way of launching hypersonic vehicles."

NASA Armstrong has a long history of pioneering hypersonic research, including the X-15 rocket plane program of the 1960s in which one mission hit Mach 6.7 (4,520 mph). In the early 2000s, NASA Armstrong flew three 12-foot-long, uncrewed X-43 aircraft, with the final flight hitting Mach 9.6 (6,363 mph).

At present, hypersonic testing is primarily done with rockets or by air launches with a highly modified B-52 bomber.

"TGALS could be an alternate method of getting (hypersonic vehicles) to the range," said Craig Stephens, an [aerospace engineer](#) at NASA Armstrong. "It may be a simpler system to use. You may be able to have a bit more flexibility when you launch."

Stevens worked on thermal structure testing of control surfaces for the X-37 spaceplane, a vehicle that hits speeds of nearly Mach 25 (approximately 19,000 mph) on re-entry.

"In my opinion, we need to work in this area," Stephens said. "Other countries are definitely working on it and, in some regards, may be ahead of the United States in certain areas. It's a flight regime that we need to be working in, and be focused on developing test articles and increasing our knowledge and capabilities."

Provided by NASA Armstrong Flight Research Center

Citation: NASA Armstrong develops tech to bring space launch to any airport (2022, November 3) retrieved 19 June 2024 from <https://phys.org/news/2022-11-nasa-armstrong-tech-space-airport.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.