

Rotation-based triboelectric neurostimulator for real-time modulation of stimulus parameters

November 16 2022



Credit: DGIST

The research team led by Professor Sanghoon Lee from the Department of Robotics and Mechatronics Engineering at DGSIT (President Yang Kuk) successfully developed a rotation-based triboelectric neuro-



stimulator (RoTENS) capable of real-time modulations of stimulus parameters, including current amplitude, frequency, and pulse width.

Existing neurostimulators require additional steps when adjusting <u>stimulus</u> parameters in real time due to the characteristics of its circuitbased system. In particular, changing the stimulus parameters while maintaining charge requires complex calculations and additional processes via <u>electronic devices</u>, resulting in low practicality.

Professor Sanghoon Lee's research team at DGIST modified triboelectric nanogenerators (TENG), which generate <u>electric energy</u> via friction, to a rotation-based design, generating multiple pulses with a single rotation. In addition, various pulses can be modulated for neurostimulation by changing the electrode patterns in the TENG.

Owing to the charge-generation mechanism of TENG, RoTENG enables the control of the frequency and <u>pulse</u> width while maintaining a constant charge during rotation, allowing <u>nerve stimulation</u> while controlling stimulus parameters in real time. Furthermore, adjusting the interlayer distance allows for controlling the amplitude of the pulses, indicating that various stimulus parameters (frequency, pulse width, and amplitude) can be controlled.

In vivo animal experiments were performed to verify the clinical effectiveness of RoTENS. The <u>physiological responses</u> induced by modulating the stimulus parameters by RoTENS were observed during the stimulation of the right tibial nerve in rats.

Varying the frequency (10–50 Hz) allowed the muscle to shift its physiological state smoothly from twitching to fused tetanus. Natural relaxation of the muscle was induced by changing the current amplitude via the distance between the two layers (0–6 mm). These results indicate that RoTENS is sufficient to induce the desired physiological response



while creating a wide range of frequencies and amplitudes.

Professor Sanghoon Lee (Robotics and Mechatronics Engineering, DGIST) said that preclinical trials with the newly developed neurostimulators proves that it is possible to control the stimulus parameters for neural stimulation in real time with rotational energy.

The researchers expect that <u>technological advancements</u> and further optimization research will lead to new opportunities and possibilities for the use of TENG as neurostimulators, such as immediate and intuitive sensory feedback to bionic limbs or exoskeletons, rehabilitation, and bioelectric medicine.

This research was published in the journal Nano Energy.

More information: Minseok Kang et al, Triboelectric neurostimulator for physiological modulation of leg muscle, *Nano Energy* (2022). <u>DOI:</u> <u>10.1016/j.nanoen.2022.107861</u>

Provided by DGIST (Daegu Gyeongbuk Institute of Science and Technology)

Citation: Rotation-based triboelectric neurostimulator for real-time modulation of stimulus parameters (2022, November 16) retrieved 2 May 2024 from https://phys.org/news/2022-11-rotation-based-triboelectric-neurostimulator-real-time-modulation.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.