


Researchers develop all-optical approach to pumping chip-based nanolasers

December 15 2022



Researchers have developed a new all-optical method for driving multiple high density nanolaser arrays using light traveling down a single optical fiber. The optical driver creates programmable patterns of light via interference. Credit: Myung-Ki Kim, Korea University

Researchers have developed a new all-optical method for driving

multiple highly dense nanolaser arrays. The approach could enable chip-based optical communication links that process and move data faster than today's electronic-based devices.

"The development of optical interconnects equipped with high-density nanolasers would improve information processing in the [data centers](#) that move information across the internet," said research team leader Myung-Ki Kim from Korea University.

"This could allow streaming of ultra-high-definition movies, enable larger-scale interactive online encounters and games, accelerate the expansion of the Internet of Things and provide the fast connectivity needed for big data analytics."

The research, published in *Optica*, demonstrates that densely integrated nanolaser arrays—in which the lasers are just 18 microns apart—can be fully driven and programmed with light from a single optical fiber.

"Optical devices integrated onto a chip are a promising alternative to electronic integrated devices, which are struggling to keep up with today's data processing demands," said Kim.

"By eliminating the large and complex electrodes typically used to drive laser arrays, we reduced the overall dimensions of the laser [array](#) while also eliminating the heat generation and processing delays that come with electrode-based drivers."


Replacing electrodes with light

The new nanolasers could be used in optical integrated circuit systems, which detect, generate, transmit and process information on a microchip via light. Instead of the fine copper wires used in electronic chips, optical circuits use optical waveguides, which allow much higher

bandwidths while generating less heat. However, because the size of optical integrated circuits is quickly reaching into the nanometer regime, there is a need for new ways to drive and control their nano-sized light sources efficiently.

To emit light, lasers need to be supplied with energy in a process called pumping. For nanolaser arrays, this is typically accomplished using a pair of electrodes for each laser within an array, which requires significant on-chip space and energy consumption while also causing processing delays.

To overcome this critical limitation, the researchers replaced these electrodes with a unique optical driver that creates programmable patterns of light via interference. This pump light travels through an [optical fiber](#) onto which nanolasers are printed.



These simulation images show how the light interference pattern interacts with the nanolaser arrays. (a) Schematic of spatial interference between TE₀₀ and TE₀₁ modes along the microfiber. Here, two photonic crystal nanobeam lasers (PCN₁ and PCN₂) are attached to the surface of the microfiber in a line. (b) Difference in effective refractive index (Δn) of TE₀₀ and TE₀₁ modes and corresponding half beat length (L_{π}), (c) Log $|E|^2$ profile of PCN cavity mode in

the xy-plane and SEM image of fabricated InGaAsP PCN laser. (d, e) $|E|^2$ profiles of the pump beam in the xz- and yz-planes, respectively, where the beam propagates from left to right. (f) Absorbed power density profiles along the xy-plane at the vertical center of PCNs. Credit: Korea University

To demonstrate this approach, the researchers used a high-resolution transfer-printing technique to fabricate multiple photonic crystal nanolasers spaced 18 microns apart. These arrays were applied onto the surface of a 2-micron-diameter optical microfiber.

This had to be done in a way that precisely aligned the nanolaser arrays with the [interference pattern](#). The interference pattern could also be modified by adjusting the driving beam's polarization and pulse width.

Laser driving with a single fiber

The experiments showed that the design allowed multiple nanolaser arrays to be driven using light traveling through a single fiber. The results matched well with numerical calculations and showed that the printed [nanolaser](#) arrays could be fully controlled by the pump beam interference patterns.

"Our all-optical laser driving and programming technology can also be applied to chip-based silicon photonics systems, which could play a key role in the development of chip-to-chip or on-chip optical interconnects," said Kim.

"However, it would be necessary to prove how independently the modes of a silicon waveguide can be controlled. If this can be done, it would be a huge leap forward in the advancement of on-chip optical interconnects and optical integrated circuits."

More information: Myung-Ki Kim et al, Three-dimensional programming of nanolaser arrays through a single optical microfiber, *Optica* (2022). [DOI: 10.1364/OPTICA.471715](https://doi.org/10.1364/OPTICA.471715)

Provided by Optica

Citation: Researchers develop all-optical approach to pumping chip-based nanolasers (2022, December 15) retrieved 26 April 2024 from <https://phys.org/news/2022-12-all-optical-approach-chip-based-nanolasers.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.